

821227

County Kandiyohi
Quad Sunburg
Quad ID 143C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date

Update Date 11/08/2016

Received Date 10/17/2016

Well Name HUSAK, STEVE	Township 121	Range 35	Dir W	Section 6	Subsection CACCBC																									
Elevation 1207	Elev. Method LiDAR 1m DEM (MNDNR)																													
Address Well 5962 193RD AV NW PENNOCK MN Contact 971 OTTO ST ST PAUL MN 55102																														
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOPSOIL</td><td>0</td><td>2</td><td></td><td></td></tr><tr><td>SANDY CLAY</td><td>2</td><td>23</td><td>YELLOW</td><td></td></tr><tr><td>CLAY</td><td>23</td><td>44</td><td>GRAY</td><td></td></tr><tr><td>SAND: COARSE</td><td>44</td><td>65</td><td></td><td></td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOPSOIL	0	2			SANDY CLAY	2	23	YELLOW		CLAY	23	44	GRAY		SAND: COARSE	44	65		
Geological Material	From	To (ft.)	Color	Hardness																										
TOPSOIL	0	2																												
SANDY CLAY	2	23	YELLOW																											
CLAY	23	44	GRAY																											
SAND: COARSE	44	65																												
Well Depth 65 ft. Depth Completed 65 ft. Date Well Completed 10/07/2016																														
Drill Method Non-specified Rotary Drill Fluid Bentonite																														
Use domestic Status Active																														
Well Hydrofractured? Yes ☐ No ☒ From To																														
Casing Type Single casing Joint																														
Drive Shoe? Yes ☐ No ☒ Above/Below																														
Casing Diameter 5 in. Weight 60 lbs./ft. Hole Diameter 3.7 in. To ft.																														
Open Hole From ft. To ft.																														
Screen? ☒ Type plastic Make JOHNSON																														
Diameter 5 in. Slot/Gauze 15 Length 5 ft. Set 60 ft. To 65 ft.																														
Static Water Level 22 ft. land surface Measure 07/27/2016																														
Pumping Level (below land surface) 34 ft. 2 hrs. Pumping at 20 g.p.m.																														
Wellhead Completion Pitless adapter manufacturer MERRILL Model MCK ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																														
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																														
Material bentonite Amount 5 Sacks From To ft. 55 ft.																														
Nearest Known Source of Contamination 50 feet Direction Septic tank/drain field Type																														
Well disinfected upon completion? ☒ Yes ☐ No																														
Pump ☐ Not Installed Date Installed 10/07/2016																														
Manufacturer's name FLOWISE																														
Model Number P10S05 HP 0.5 Volt 230																														
Length of drop pipe 40 ft Capacity 10 g.p. Typ Submersible																														
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																														
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																														
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 333273 Y 5020195 Unique Number Verification Address verification Input Date 11/08/2016																														
Angled Drill Hole																														
Well Contractor Thein Well Co., Inc. 1337 JOHNSON, J. Licensee Business Lic. or Reg. No. Name of Driller																														
Minnesota Well Index Report		821227		Printed on 10/02/2026 HE-01205-15																										