

822648

County Douglas
Quad Quam Lake
Quad ID 181B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date08/16/2017
Update Date01/26/2021
Received Date03/27/2017

Well Name JOHNSON, RON Elevation1343 Address C/W7266 55 CR EVANSVILLE MN 56326 Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>2</td><td></td><td></td></tr><tr><td>CLAY</td><td>2</td><td>30</td><td>YELLOW</td><td></td></tr><tr><td>CLAY</td><td>30</td><td>117</td><td>BLUE</td><td></td></tr><tr><td>SAND 20 SLOT</td><td>117</td><td>130</td><td>GRAY</td><td></td></tr></table>	Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	2			CLAY	2	30	YELLOW		CLAY	30	117	BLUE		SAND 20 SLOT	117	130	GRAY		Well Depth130 ft. Drill MethodNon-specified Rotary Use domestic Well Hydrofractured? Yes No Casing TypeSingle casing Drive Shoe? Yes No Casing Diameter5 in. Weight120 ft. Open Hole <table><tr><td>From</td><td>ft.</td><td>To</td><td>ft.</td></tr></table> Screen? X Typestainless MakeJOHNSON Diameter5 in. Slot/Gauze20 Length10 ft. Set120 ft. Static Water Level 58 ft. land surface Measure 12/28/2016 Pumping Level (below land surface) ft. hrs. Pumping at 60 g.p.m. Wellhead Completion Pitless adapter manufacturer BULLDOG Model Casing Protection 12 in. above grade At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? X Yes No Not Specified Material Amount From To bentonite ft. 60 ft. Nearest Known Source of Contamination 70 feet East Direction Well disinfected upon completion? X Yes No Sewer Type Pump Not Installed Date Installed Manufacturer's name FLOWISE Model Number HP 0.5 Volt 230 Length of drop pipe 90 ft Capacity 10 g.p. Typ Submersible Abandoned Does property have any not in use and not sealed well(s)? Yes No Variance Was a variance granted from the MDH for this well? Yes No Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 292531 Y 5094081 Unique Number Verification Address verification Input Date 01/04/2021 Angled Drill Hole Well Contractor Waskosky Well Drilling 1581 DAVE/GORDY Licensee Business Lic. or Reg. No. Name of Driller	From	ft.	To	ft.
Geological Material	From	To (ft.)	Color	Hardness																										
TOP SOIL	0	2																												
CLAY	2	30	YELLOW																											
CLAY	30	117	BLUE																											
SAND 20 SLOT	117	130	GRAY																											
From	ft.	To	ft.																											