

839199

County Otter Tail
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 08/27/2021
Received Date 07/24/2019

Well Name SINNA, MIKE	Township 135	Range 40	Dir W	Section 6	Subsection CCC	Well Depth 60 ft.	Depth Completed 60 ft.	Date Well Completed 07/03/2019																														
Elevation						Drill Method Non-specified Rotary	Drill Fluid Bentonite																															
Address						Use domestic	Status Active																															
Well 390TH ST DENT MN 56528						Well Hydrofractured? Yes ☐ No ☒ From To																																
Stratigraphy Information						Casing Type Single casing Joint																																
<table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>3</td><td>BLACK</td><td>SOFT</td></tr><tr><td>SILTY SAND</td><td>3</td><td>17</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>17</td><td>21</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SANDY GRAVEL</td><td>21</td><td>27</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND FINE</td><td>27</td><td>60</td><td>GRAY</td><td>MEDIUM</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	3	BLACK	SOFT	SILTY SAND	3	17	GRAY	SOFT	CLAY	17	21	GRAY	MEDIUM	SANDY GRAVEL	21	27	GRAY	MEDIUM	SAND FINE	27	60	GRAY	MEDIUM	Drive Shoe? Yes ☐ No ☐ Above/Below		
Geological Material	From	To (ft.)	Color	Hardness																																		
TOP SOIL	0	3	BLACK	SOFT																																		
SILTY SAND	3	17	GRAY	SOFT																																		
CLAY	17	21	GRAY	MEDIUM																																		
SANDY GRAVEL	21	27	GRAY	MEDIUM																																		
SAND FINE	27	60	GRAY	MEDIUM																																		
<table><tr><td>Casing Diameter</td><td colspan="2">Weight</td><td colspan="2">Hole Diameter</td></tr><tr><td>4 in. To</td><td>55 ft.</td><td>lbs./ft.</td><td>7.7 in. To</td><td>20 ft.</td></tr><tr><td></td><td></td><td></td><td>6.7 in. To</td><td>60 ft.</td></tr></table>						Casing Diameter	Weight		Hole Diameter		4 in. To	55 ft.	lbs./ft.	7.7 in. To	20 ft.				6.7 in. To	60 ft.																		
Casing Diameter	Weight		Hole Diameter																																			
4 in. To	55 ft.	lbs./ft.	7.7 in. To	20 ft.																																		
			6.7 in. To	60 ft.																																		
Open Hole						<table><tr><td>From</td><td>ft.</td><td>To</td><td>ft.</td></tr><tr><td>Screen? ☒</td><td>Type mixed</td><td>Make JOHNSON</td><td></td></tr><tr><td>Diameter</td><td>Slot/Gauze</td><td>Length</td><td>Set</td></tr><tr><td>4 in.</td><td>12</td><td>5 ft.</td><td>55 ft. 60 ft.</td></tr></table>			From	ft.	To	ft.	Screen? ☒	Type mixed	Make JOHNSON		Diameter	Slot/Gauze	Length	Set	4 in.	12	5 ft.	55 ft. 60 ft.														
From	ft.	To	ft.																																			
Screen? ☒	Type mixed	Make JOHNSON																																				
Diameter	Slot/Gauze	Length	Set																																			
4 in.	12	5 ft.	55 ft. 60 ft.																																			
Static Water Level						<table><tr><td>4 ft.</td><td>land surface</td><td>Measure</td><td>07/03/2019</td></tr></table>			4 ft.	land surface	Measure	07/03/2019																										
4 ft.	land surface	Measure	07/03/2019																																			
Pumping Level (below land surface)						<table><tr><td>30 ft.</td><td>2 hrs.</td><td>Pumping at</td><td>20 g.p.m.</td></tr></table>			30 ft.	2 hrs.	Pumping at	20 g.p.m.																										
30 ft.	2 hrs.	Pumping at	20 g.p.m.																																			
Wellhead Completion						<table><tr><td>Pitless adapter manufacturer</td><td>SUMMON</td><td>Model</td></tr><tr><td>☐ Casing Protection</td><td>☐ 12 in. above grade</td><td></td></tr><tr><td colspan="3">☐ At-grade (Environmental Wells and Borings ONLY)</td></tr></table>			Pitless adapter manufacturer	SUMMON	Model	☐ Casing Protection	☐ 12 in. above grade		☐ At-grade (Environmental Wells and Borings ONLY)																							
Pitless adapter manufacturer	SUMMON	Model																																				
☐ Casing Protection	☐ 12 in. above grade																																					
☐ At-grade (Environmental Wells and Borings ONLY)																																						
Grouting Information						<table><tr><td>Well Grouted?</td><td>☒ Yes</td><td>☐ No</td><td>☐ Not Specified</td></tr><tr><td>Material</td><td>Amount</td><td>From</td><td>To</td></tr><tr><td>bentonite</td><td>2 Sacks</td><td>ft.</td><td>40 ft.</td></tr></table>			Well Grouted?	☒ Yes	☐ No	☐ Not Specified	Material	Amount	From	To	bentonite	2 Sacks	ft.	40 ft.																		
Well Grouted?	☒ Yes	☐ No	☐ Not Specified																																			
Material	Amount	From	To																																			
bentonite	2 Sacks	ft.	40 ft.																																			
Nearest Known Source of Contamination						<table><tr><td><u>70</u> feet</td><td><u>South</u> Direction</td><td><u>Septic tank/drain field</u> Type</td></tr><tr><td>Well disinfected upon completion?</td><td>☐ Yes</td><td>☐ No</td></tr></table>			<u>70</u> feet	<u>South</u> Direction	<u>Septic tank/drain field</u> Type	Well disinfected upon completion?	☐ Yes	☐ No																								
<u>70</u> feet	<u>South</u> Direction	<u>Septic tank/drain field</u> Type																																				
Well disinfected upon completion?	☐ Yes	☐ No																																				
Pump						<table><tr><td>☐ Not Installed</td><td>Date Installed</td><td><u>07/03/2019</u></td></tr><tr><td>Manufacturer's name</td><td colspan="2">LEGEND</td></tr><tr><td>Model Number</td><td><u>FM52LD10S</u></td><td>HP <u>0.5</u> Volt <u>230</u></td></tr><tr><td>Length of drop pipe</td><td><u>40</u> ft</td><td>Capacity <u>10</u> g.p. Typ <u>Submersible</u></td></tr></table>			☐ Not Installed	Date Installed	<u>07/03/2019</u>	Manufacturer's name	LEGEND		Model Number	<u>FM52LD10S</u>	HP <u>0.5</u> Volt <u>230</u>	Length of drop pipe	<u>40</u> ft	Capacity <u>10</u> g.p. Typ <u>Submersible</u>																		
☐ Not Installed	Date Installed	<u>07/03/2019</u>																																				
Manufacturer's name	LEGEND																																					
Model Number	<u>FM52LD10S</u>	HP <u>0.5</u> Volt <u>230</u>																																				
Length of drop pipe	<u>40</u> ft	Capacity <u>10</u> g.p. Typ <u>Submersible</u>																																				
Abandoned						<table><tr><td>Does property have any not in use and not sealed well(s)?</td><td>☐ Yes</td><td>☒ No</td></tr></table>			Does property have any not in use and not sealed well(s)?	☐ Yes	☒ No																											
Does property have any not in use and not sealed well(s)?	☐ Yes	☒ No																																				
Variance						<table><tr><td>Was a variance granted from the MDH for this well?</td><td>☐ Yes</td><td>☒ No</td></tr></table>			Was a variance granted from the MDH for this well?	☐ Yes	☒ No																											
Was a variance granted from the MDH for this well?	☐ Yes	☒ No																																				
Miscellaneous						<table><tr><td>First Bedrock</td><td>Aquifer</td><td></td></tr><tr><td>Last Strat</td><td>Depth to Bedrock</td><td>ft</td></tr><tr><td>Located by</td><td></td><td></td></tr><tr><td>Locate Method</td><td></td><td></td></tr><tr><td>System</td><td>UTM - NAD83, Zone 15, Meters</td><td>X Y</td></tr><tr><td>Unique Number Verification</td><td></td><td>Input Date</td></tr></table>			First Bedrock	Aquifer		Last Strat	Depth to Bedrock	ft	Located by			Locate Method			System	UTM - NAD83, Zone 15, Meters	X Y	Unique Number Verification		Input Date												
First Bedrock	Aquifer																																					
Last Strat	Depth to Bedrock	ft																																				
Located by																																						
Locate Method																																						
System	UTM - NAD83, Zone 15, Meters	X Y																																				
Unique Number Verification		Input Date																																				
Angled Drill Hole																																						
Well Contractor						<table><tr><td>Antonsen Well Drilling, Inc.</td><td>2147</td><td>FELL, R</td></tr><tr><td>Licensee Business</td><td>Lic. or Reg. No.</td><td>Name of Driller</td></tr></table>			Antonsen Well Drilling, Inc.	2147	FELL, R	Licensee Business	Lic. or Reg. No.	Name of Driller																								
Antonsen Well Drilling, Inc.	2147	FELL, R																																				
Licensee Business	Lic. or Reg. No.	Name of Driller																																				
Remarks																																						