

850872

County Becker
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 04/30/2026
Received Date 02/02/2026

Well Name SEABERG, V.	Township 140	Range 24	Dir W	Section 36	Subsection CAA	Well Depth 236 ft.	Depth Completed 236 ft.	Date Well Completed 05/15/2025																																												
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite																																													
Address C/W 23406 104 CR DETROIT LAKES MN 56501						Use domestic	Status Active																																													
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>1</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>1</td><td>58</td><td>BROWN</td><td>HARD</td></tr><tr><td>CLAY</td><td>58</td><td>103</td><td>GRAY</td><td>HARD</td></tr><tr><td>CLAYSTONE</td><td>103</td><td>127</td><td>GRAY</td><td>HARD</td></tr><tr><td>ROCKS</td><td>127</td><td>134</td><td>GRAY</td><td>HARD</td></tr><tr><td>CLAY</td><td>134</td><td>148</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>148</td><td>223</td><td>GRAY</td><td>HARD</td></tr><tr><td>WATERSAND</td><td>223</td><td>236</td><td>GRAY</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	1	BLACK	SOFT	CLAY	1	58	BROWN	HARD	CLAY	58	103	GRAY	HARD	CLAYSTONE	103	127	GRAY	HARD	ROCKS	127	134	GRAY	HARD	CLAY	134	148	GRAY	SOFT	CLAY	148	223	GRAY	HARD	WATERSAND	223	236	GRAY	SOFT	Well Hydrofractured? Yes ☐ No ☒ From To	
						Geological Material	From	To (ft.)	Color	Hardness																																										
						TOP SOIL	0	1	BLACK	SOFT																																										
						CLAY	1	58	BROWN	HARD																																										
						CLAY	58	103	GRAY	HARD																																										
						CLAYSTONE	103	127	GRAY	HARD																																										
						ROCKS	127	134	GRAY	HARD																																										
						CLAY	134	148	GRAY	SOFT																																										
						CLAY	148	223	GRAY	HARD																																										
						WATERSAND	223	236	GRAY	SOFT																																										
Casing Type Single casing Joint																																																				
Drive Shoe? Yes ☐ No ☒ Above/Below																																																				
Casing Diameter 4 in. To 232 ft. 1.9 lbs./ft.																																																				
Weight																																																				
Hole Diameter 6.7 in. To 236 ft.																																																				
Open Hole From ft. To ft.																																																				
Screen? ☒ Type stainless Make JOHNSON																																																				
Diameter 4 in. Slot/Gauze 20 Length 4 ft. Set 232 ft. To 236 ft.																																																				
Static Water Level 130 ft. land surface Measure 05/15/2025																																																				
Pumping Level (below land surface) 150 ft. 4 hrs. Pumping at 35 g.p.m.																																																				
Wellhead Completion Pitless adapter manufacturer BAKER Model 4AD ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																				
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 4 Sacks ft. 80 ft.																																																				
Nearest Known Source of Contamination 54 feet Southwes Direction Other Type Well disinfected upon completion? ☒ Yes ☐ No																																																				
Pump ☐ Not Installed Date Installed 05/15/2025 Manufacturer's name SCHAEFER Model Number 6105S HP 0.75 Volt 230 Length of drop pipe 150 ft Capacity 10 g.p. Typ Submersible																																																				
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																																				
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																																				
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																																				
Angled Drill Hole																																																				
Well Contractor Cormorant Well And Pump 1498 VAREBERG, S. Licensee Business Lic. or Reg. No. Name of Driller																																																				