

851097

County Beltrami
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 08/06/2025
Received Date 01/24/2022

Well Name MAHER, RILEY					Township 150	Range 33	Dir Section W 10	Subsection BAD	Well Depth 200 ft.		Depth Completed 200 ft.		Date Well Completed 07/21/2021																										
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid																											
Address C/W 26177 IRVINE AV NE PUPOSKY MN 56667									Use domestic		Status Sealed																												
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>32</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SLAY + FINE SAND</td><td>32</td><td>34</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SILT MUDDY</td><td>34</td><td>42</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>42</td><td>200</td><td>GRAY</td><td>MEDIUM</td></tr></table>									Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	32	GRAY	MEDIUM	SLAY + FINE SAND	32	34	BROWN	SOFT	SILT MUDDY	34	42	GRAY	SOFT	CLAY	42	200	GRAY	MEDIUM	Well Hydrofractured? Yes ☐ No ☐		From		To	
									Geological Material	From	To (ft.)	Color	Hardness																										
									CLAY	0	32	GRAY	MEDIUM																										
									SLAY + FINE SAND	32	34	BROWN	SOFT																										
									SILT MUDDY	34	42	GRAY	SOFT																										
									CLAY	42	200	GRAY	MEDIUM																										
									Casing Type					Joint																									
									Drive Shoe? Yes ☐ No ☐					Above/Below																									
																			Hole Diameter																				
																			8 in. To 50 ft.																				
										6.5 in. To 200 ft.																													
Open Hole									From		ft.		To		ft.																								
Screen? ☐									Type			Make																											
Static Water Level																																							
Pumping Level (below land surface)																																							
Wellhead Completion Pitless adapter manufacturer ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY) Model																																							
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To driven casing seal 11 Sacks 0 ft. 200 ft.																																							
Nearest Known Source of Contamination feet Direction Type Well disinfected upon completion? ☐ Yes ☐ No																																							
Pump ☐ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																																							
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																							
Miscellaneous First Bedrock Last Strat Aquifer Located by Depth to Bedrock ft Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																							
Angled Drill Hole																																							
Well Contractor Bradseth Well Drilling 2134 BRADSETH, C Licensee Business Lic. or Reg. No. Name of Driller																																							

Remarks
NEEDS FUNDING TO DIG DEEPER
SEALED 7/21/2021 BY 2134