

Minnesota Unique Well Number

851780

County Aitkin

Quad

Quad ID

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date

11/03/2020

Update Date

11/03/2020

Received Date

09/14/2020

Well Name	Township	Range	Dir	Section	Subsection	Well Depth	Depth Completed	Date Well Completed			
DOBSON, DAN	49	23	W	27	ACA	203 ft.	203 ft.	07/15/2020			
Elevation	Elev. Method					Drill Method	Non-specified Rotary	Drill Fluid	Bentonite		
Address						Use	domestic	Status	Active		
						Well Hydrofractured?	Yes ☐	No ☒	From	To	
C/W 18328 476TH ST MCGREGOR MN 55760						Casing Type	Single casing	Joint			
						Drive Shoe?	Yes ☐	No ☐	Above/Below		
Stratigraphy Information						Casing Diameter	Weight	Hole Diameter			
Geological Material		From	To (ft.)	Color	Hardness	4 in. To	195 ft.	lbs./ft.	6.5 in. To 203 ft.		
SAND		0	17	BROWN	MEDIUM						
CLAY		17	100	GRAY							
SAND		100	103	BROWN							
CLAY + GRAVEL		103	190	GRAY							
SAND		190	203	BROWN							
						Open Hole	From	ft.	To	ft.	
						Screen?	☒	Type	stainless	Make	JOHNSON
						Diameter	Slot/Gauze	Length	Set		
						2 in.	10	8 ft.	195 ft.	203 ft.	
						Static Water Level					
						15 ft.	land surface	Measure	07/15/2020		
						Pumping Level (below land surface)					
						160 ft.	1 hrs.	Pumping at	50 g.p.m.		
						Wellhead Completion					
						Pitless adapter manufacturer					
☐ Casing Protection						☒ 12 in. above grade					
☐ At-grade (Environmental Wells and Borings ONLY)											
Grouting Information						Well Grouted?	☒ Yes	☐ No	☐ Not Specified		
Material		Amount		From	To						
bentonite		8 Sacks		ft.	50 ft.						
Nearest Known Source of Contamination						50 feet	Direction		Type		
Well disinfected upon completion?						☒ Yes	☐ No				
Pump						☒ Not Installed	Date Installed				
Manufacturer's name											
Model Number		HP		Volt							
Length of drop pipe		ft	Capacity	g.p.	Typ						
Abandoned						Does property have any not in use and not sealed well(s)?					
						☐ Yes	☒ No				
Variance						Was a variance granted from the MDH for this well?					
						☐ Yes	☒ No				
Miscellaneous						First Bedrock					
						Last Strat					
						Aquifer					
						Depth to Bedrock					
						ft					
Located by											
Locate Method											
System		UTM - NAD83, Zone 15, Meters		X		Y					
Unique Number Verification						Input Date					
Angled Drill Hole											
Well Contractor						Hasskamp Bros. Well Drilling					
						1585		CORY + CHAD			
Licensee Business						Lic. or Reg. No.		Name of Driller			

Minnesota Well Index Report

851780

Printed on 08/13/2026

HE-01205-15