

Minnesota Unique Well Number

852329

CountyLac Qui
QuadMilan
Quad ID130C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date10/27/2020
Update Date10/27/2020
Received Date10/15/2020

Well Name SSCHILDT,	Township 118	Range 42	Dir W	Section 27	Subsection DBBBAB	Well Depth 129 ft.	Depth Completed 129 ft.	Date Well Completed 09/30/2020
Elevation 1027	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address C/W 225 BROADWAY AV MONTEVIDEO MN 56265						Use domestic	Status Active	
Stratigraphy Information						Well Hydrofractured? Yes ☐ No ☒	From To	
Geological Material						Casing Type Single casing	Joint	
CLAY						Drive Shoe? Yes ☐ No ☒	Above/Below	
CLAY						Casing Diameter 4 in.	Weight 119 ft.	Hole Diameter 6.5 in.
SAND								129 ft.
						Open Hole From ft. To ft.		
						Screen? ☒	Type telescoping	Make JOHNSON
						Diameter 4 in.	Slot/Gauze 18	Length 10 ft.
							Set 119 ft.	129 ft.
						Static Water Level 78 ft.	land surface	Measure 10/05/2020
						Pumping Level (below land surface) 79 ft.	hrs.	Pumping at 20 g.p.m.
						Wellhead Completion		
						Pitless adapter manufacturer MERRILL	Model SPK	
						☐ Casing Protection	☐ 12 in. above grade	
						☐ At-grade (Environmental Wells and Borings ONLY)		
						Grouting Information	Well Grouted? ☒ Yes ☐ No ☐ Not Specified	
						Material high solids bentonite	Amount 5 Sacks	From To ft. 60 ft.
						Nearest Known Source of Contamination 60 feet	Direction	Sewer Type
						Well disinfected upon completion? ☒ Yes ☐ No		
						Pump ☐ Not Installed	Date Installed 10/05/2020	
						Manufacturer's name GRUNDFOS		
						Model Number 10SQE07-	HP 0.75	Volt 230
						Length of drop pipe 100 ft	Capacity 15 g.p.	Typ Submersible
						Abandoned Does property have any not in use and not sealed well(s)?	☐ Yes ☐ No	
						Variance Was a variance granted from the MDH for this well?	☐ Yes ☒ No	
						Miscellaneous		
						First Bedrock	Aquifer	Quat. buried
						Last Strat sand-gray	Depth to Bedrock	ft
						Located by Minnesota Geological Survey		
						Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or		
						System UTM - NAD83, Zone 15, Meters	X 270767	Y 4987115
						Unique Number Verification Info/GPS from data	Input Date 10/27/2020	
						Angled Drill Hole		
						Well Contractor		
						Steffl Drilling and Pump, Inc.	1551	STEFFL, T.
						Licensee Business	Lic. or Reg. No.	Name of Driller
Remarks								

Minnesota Well Index Report

852329

Printed on 08/13/2026
HE-01205-15