

854018

County Washington
Quad Prescott
Quad ID 102D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date02/25/2025
Update Date11/20/2025
Received Date02/18/2025

Well Name CREATIVE					Township 27		Range 20		Dir Section W 4		Subsection DABCBB		Well Depth 265 ft.			Depth Completed 265 ft.			Date Well Completed 01/28/2025										
Elevation 912.1		Elev. Method LiDAR 1m DEM (MNDNR)												Drill Method Dual Rotary			Drill Fluid Foam												
Address															Use domestic			Status Active											
Well					14760 65TH ST S HASTINGS MN 55033										Well Hydrofractured? Yes ☐ No ☒			From To											
Contact					707 COMMERCE DR WOODBURY MN 55125										Casing Type Single casing			Joint Welded											
Stratigraphy Information															Drive Shoe? Yes ☒ No ☐			Above/Below											
Geological Material					From		To (ft.)		Color		Hardness		Casing Diameter			Weight			Hole Diameter										
CLAY					0		5						6 in. To			220 ft. 18.97 lbs./ft.			10 in. To 220 ft.										
SANDSTONE					5		45		YELLOW		SOFT								6 in. To 265 ft.										
SANDSTONE					45		100		YELLOW		MEDIUM																		
SANDSTONE					100		150		GRAY		HARD																		
SANDSTONE					150		265		GRAY		MEDIUM																		
															Open Hole			From		220 ft.		To		265 ft.					
															Screen?			☐		Type		Make							
Static Water Level															160 ft.			land surface			Measure			02/03/2025					
Pumping Level (below land surface)															180 ft.			1 hrs.		Pumping at			15 g.p.m.						
Wellhead Completion															Pitless adapter manufacturer			BAKER			Model			6J1					
☒ Casing Protection															☒ 12 in. above grade														
☐ At-grade (Environmental Wells and Borings ONLY)																													
Grouting Information															Well Grouted?			☒ Yes		☐ No		☐ Not Specified							
Material										Amount					From		To												
neat cement										5 Cubic yards					ft. 220		ft.												
Nearest Known Source of Contamination															50 feet			Southwes Direction			Sewer Type								
Well disinfected upon completion?															☒ Yes		☐ No												
Pump															☐ Not Installed		Date Installed			02/03/2025									
Manufacturer's name															GRUNDFOS														
Model Number					15/15/290					HP		1.5		Volt		230													
Length of drop pipe					180 ft					Capacity		15 g.p.		Typ		Submersible													
Abandoned															Does property have any not in use and not sealed well(s)?										☐ Yes		☒ No		
Variance															Was a variance granted from the MDH for this well?										☐ Yes		☒ No		
Miscellaneous															First Bedrock										Aquifer				
Last Strat																									Depth to Bedrock			ft	
Located by															Minnesota Geological Survey														
Locate Method															Digitization (Screen) - Map (1:24,000) (15 meters or														
System					UTM - NAD83, Zone 15, Meters					X 515317		Y 4966729																	
Unique Number Verification					Information from					Input Date		02/25/2025																	
Angled Drill Hole																													
Well Contractor															Tim Butterfield Drilling, Inc.										2660		BUTTERFIELD,T		
Licensee Business															Lic. or Reg. No.										Name of Driller				