

860520

County Anoka
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date06/06/2023
Update Date06/06/2023
Received Date10/14/2021

Well NameTownshipRangeDir SectionSubsection GAGNER, TYLER 3323W 35CBB ElevationElev. Method					Well DepthDepth CompletedDate Well Completed 65 ft.60 ft.09/22/2021 Drill MethodNon-specified RotaryDrill FluidBentonite																																																																																																																														
Address C/W18340 LAKEVIEW DR NE WYOMING MN 55092					Use domesticStatusActive Well Hydrofractured?YesNoFromTo Casing TypeStep downJoint Drive Shoe?YesNoAbove/Below																																																																																																																														
Stratigraphy Information <table><thead><tr><th>Geological Material</th><th>From</th><th>To (ft.)</th><th>Color</th><th>Hardness</th></tr></thead><tbody><tr><td>FINE SAND</td><td>0</td><td>13</td><td></td><td></td></tr><tr><td>FINE SAND W/ TAN</td><td>13</td><td>34</td><td>TAN</td><td></td></tr><tr><td>FINE SAND</td><td>34</td><td>52</td><td></td><td></td></tr><tr><td>SAND</td><td>52</td><td>62</td><td></td><td></td></tr><tr><td>COARSE SAND</td><td>62</td><td>65</td><td></td><td></td></tr></tbody></table>					Geological Material	From	To (ft.)	Color	Hardness	FINE SAND	0	13			FINE SAND W/ TAN	13	34	TAN		FINE SAND	34	52			SAND	52	62			COARSE SAND	62	65			Casing DiameterWeightHole Diameter <table><tbody><tr><td>5 in. To</td><td>55 ft.</td><td>lbs./ft.</td><td>7.8 in. To</td><td>ft.</td></tr><tr><td>5 in. To</td><td>40 ft.</td><td>lbs./ft.</td><td></td><td></td></tr></tbody></table> Open HoleFromft.Toft. Screen?☒TypeplasticMakeJOHNSON <table><tbody><tr><td>Diameter</td><td>Slot/Gauze</td><td>Length</td><td>Set</td><td></td></tr><tr><td>5 in.</td><td>10</td><td>5 ft.</td><td>55 ft.</td><td>60 ft.</td></tr></tbody></table> Static Water Level <table><tbody><tr><td>8 ft.</td><td>land surface</td><td>Measure</td><td>08/26/2021</td></tr></tbody></table> Pumping Level (below land surface) <table><tbody><tr><td>55 ft.</td><td>4 hrs.</td><td>Pumping at</td><td>15 g.p.m.</td></tr></tbody></table> Wellhead Completion <table><tbody><tr><td>Pitless adapter manufacturer</td><td>MERRILL</td><td>Model</td><td>MCK</td></tr><tr><td>☐ Casing Protection</td><td>☐ 12 in. above grade</td><td></td><td></td></tr><tr><td colspan="4">☐ At-grade (Environmental Wells and Borings ONLY)</td></tr></tbody></table> Grouting InformationWell Grouted?☒Yes☐No☐Not Specified <table><tbody><tr><td>Material</td><td>Amount</td><td>From</td><td>To</td></tr><tr><td>bentonite</td><td>4 Sacks</td><td>ft.</td><td>46 ft.</td></tr></tbody></table> Nearest Known Source of Contamination <table><tbody><tr><td>75 feet</td><td>West Direction</td><td>Septic tank/drain field</td><td>Type</td></tr><tr><td colspan="2">Well disinfected upon completion?</td><td>☐ Yes☐ No</td><td></td></tr></tbody></table> Pump☐Not InstalledDate Installed09/22/2021 <table><tbody><tr><td>Manufacturer's name</td><td>STA-RITE</td><td></td><td></td></tr><tr><td>Model Number</td><td>S10P4JP052</td><td>HP</td><td>0.5</td></tr><tr><td>Length of drop pipe</td><td>40 ft</td><td>Capacity</td><td>10 g.p.</td></tr><tr><td></td><td></td><td>Typ</td><td>Submersible</td></tr></tbody></table> Abandoned Does property have any not in use and not sealed well(s)?☐ Yes☒ No Variance Was a variance granted from the MDH for this well?☐ Yes☒ No Miscellaneous <table><tbody><tr><td>First Bedrock</td><td>Aquifer</td></tr><tr><td>Last Strat</td><td>Depth to Bedrockft</td></tr><tr><td colspan="2">Located by</td></tr><tr><td>Locate Method</td><td></td></tr><tr><td>System</td><td>UTM - NAD83, Zone 15, Meters</td></tr><tr><td>Unique Number Verification</td><td>X Y</td></tr><tr><td></td><td>Input Date</td></tr></tbody></table> Angled Drill Hole Well Contractor <table><tbody><tr><td>Thein Well Co., Inc.</td><td>1337</td><td>DREXLER, M</td></tr><tr><td>Licensee Business</td><td>Lic. or Reg. No.</td><td>Name of Driller</td></tr></tbody></table>					5 in. To	55 ft.	lbs./ft.	7.8 in. To	ft.	5 in. To	40 ft.	lbs./ft.			Diameter	Slot/Gauze	Length	Set		5 in.	10	5 ft.	55 ft.	60 ft.	8 ft.	land surface	Measure	08/26/2021	55 ft.	4 hrs.	Pumping at	15 g.p.m.	Pitless adapter manufacturer	MERRILL	Model	MCK	☐ Casing Protection	☐ 12 in. above grade			☐ At-grade (Environmental Wells and Borings ONLY)				Material	Amount	From	To	bentonite	4 Sacks	ft.	46 ft.	75 feet	West Direction	Septic tank/drain field	Type	Well disinfected upon completion?		☐ Yes ☐ No		Manufacturer's name	STA-RITE			Model Number	S10P4JP052	HP	0.5	Length of drop pipe	40 ft	Capacity	10 g.p.			Typ	Submersible	First Bedrock	Aquifer	Last Strat	Depth to Bedrockft	Located by		Locate Method		System	UTM - NAD83, Zone 15, Meters	Unique Number Verification	X Y		Input Date	Thein Well Co., Inc.	1337	DREXLER, M	Licensee Business	Lic. or Reg. No.	Name of Driller
Geological Material	From	To (ft.)	Color	Hardness																																																																																																																															
FINE SAND	0	13																																																																																																																																	
FINE SAND W/ TAN	13	34	TAN																																																																																																																																
FINE SAND	34	52																																																																																																																																	
SAND	52	62																																																																																																																																	
COARSE SAND	62	65																																																																																																																																	
5 in. To	55 ft.	lbs./ft.	7.8 in. To	ft.																																																																																																																															
5 in. To	40 ft.	lbs./ft.																																																																																																																																	
Diameter	Slot/Gauze	Length	Set																																																																																																																																
5 in.	10	5 ft.	55 ft.	60 ft.																																																																																																																															
8 ft.	land surface	Measure	08/26/2021																																																																																																																																
55 ft.	4 hrs.	Pumping at	15 g.p.m.																																																																																																																																
Pitless adapter manufacturer	MERRILL	Model	MCK																																																																																																																																
☐ Casing Protection	☐ 12 in. above grade																																																																																																																																		
☐ At-grade (Environmental Wells and Borings ONLY)																																																																																																																																			
Material	Amount	From	To																																																																																																																																
bentonite	4 Sacks	ft.	46 ft.																																																																																																																																
75 feet	West Direction	Septic tank/drain field	Type																																																																																																																																
Well disinfected upon completion?		☐ Yes ☐ No																																																																																																																																	
Manufacturer's name	STA-RITE																																																																																																																																		
Model Number	S10P4JP052	HP	0.5																																																																																																																																
Length of drop pipe	40 ft	Capacity	10 g.p.																																																																																																																																
		Typ	Submersible																																																																																																																																
First Bedrock	Aquifer																																																																																																																																		
Last Strat	Depth to Bedrockft																																																																																																																																		
Located by																																																																																																																																			
Locate Method																																																																																																																																			
System	UTM - NAD83, Zone 15, Meters																																																																																																																																		
Unique Number Verification	X Y																																																																																																																																		
	Input Date																																																																																																																																		
Thein Well Co., Inc.	1337	DREXLER, M																																																																																																																																	
Licensee Business	Lic. or Reg. No.	Name of Driller																																																																																																																																	
Remarks																																																																																																																																			