

862613

County Stearns
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 08/18/2022
Received Date 06/06/2022

Well Name TERRES, BOB	Township 124	Range 33	Dir W	Section 32	Subsection DAA
Elevation	Elev. Method				
Address					
Contact 27361 363RD AV BELGRADE MN 56312					
Well 363RD AV BELGRADE MN					
Stratigraphy Information					
Geological Material	From	To (ft.)	Color	Hardness	
CLAY	0	21	YELLOW	MEDIUM	
SAND	21	26	BROWN	MEDIUM	
CLAY	26	71	BLUE	SOFT	
SAND	71	73	BLUE	MEDIUM	
CLAY-STICKY	73	88	BLUE	HARD	
SILTY CLAY	88	97	BLK/BLU	MEDIUM	
CLAY - STICKY	97	106	BLUE	HARD	
SAND/CLAY	106	121	BLUE	MEDIUM	
CLAY/SAND STRIP	121	163	BLUE	MEDIUM	
SAND/GRAVEL	163	193	WHITE	HARD	

Well Depth 193 ft.	Depth Completed 193 ft.	Date Well Completed 05/16/2022
Drill Method Non-specified Rotary	Drill Fluid Qwik gel	
Use domestic	Status Active	
Well Hydrofractured? Yes ☐ No ☒	From	To
Casing Type Single casing	Joint	
Drive Shoe? Yes ☐ No ☒	Above/Below	
Casing Diameter 5 in. To 185 ft.	Weight lbs./ft.	Hole Diameter 9 in. To 193 ft.
Open Hole	From ft.	To ft.
Screen? ☒	Type stainless	Make JOHNSON
Diameter Slot/Gauze	Length	Set
4 in. 20	8 ft.	185 ft. 193 ft.
Static Water Level		
-37 ft.	land surface	Measure 05/16/2022
Pumping Level (below land surface)		
185 ft.	3 hrs.	Pumping at 100 g.p.m.
Wellhead Completion		
Pitless adapter manufacturer		Model
☐ Casing Protection	☐ 12 in. above grade	
☐ At-grade (Environmental Wells and Borings ONLY)		
Grouting Information	Well Grouted? ☒ Yes ☐ No ☐ Not Specified	
Material	Amount	From To
cuttings		100 ft. 185 ft.
high solids bentonite	9 Sacks	ft. 100 ft.
Nearest Known Source of Contamination		
100 feet	Direction	Type
Well disinfected upon completion? ☒ Yes ☐ No		
Pump ☒	Not Installed	Date Installed
Manufacturer's name		
Model Number	HP	Volt
Length of drop pipe	ft Capacity	g.p. Typ
Abandoned		
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No		
Variance		
Was a variance granted from the MDH for this well? ☐ Yes ☒ No		
Miscellaneous		
First Bedrock	Aquifer	
Last Strat	Depth to Bedrock	ft
Located by		
Locate Method		
System	UTM - NAD83, Zone 15, Meters	X Y
Unique Number Verification	Input Date	
Angled Drill Hole		
Well Contractor		
Wheels Enterprise Inc.	3214	G RIELAND
Licensee Business	Lic. or Reg. No.	Name of Driller

Minnesota Well Index Report	862613	Printed on 10/02/2026 HE-01205-15
-----------------------------	--------	--------------------------------------