

864073

County Martin
Quad Granada
Quad ID 14A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/27/2026
Update Date 03/09/2026
Received Date 02/02/2026

Well Name GARLICK,	Township 102	Range 29	Dir W	Section 18	Subsection DBCCAB	Well Depth 165 ft.	Depth Completed 160 ft.	Date Well Completed 11/05/2025
Elevation 1145	Elev. Method LiDAR 1m DEM (MNDNR)				Drill Method Non-specified Rotary	Drill Fluid Qwik gel		
Address C/W 2557 104TH ST FAIRMONT MN 56031						Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOP SOIL 0 2 BLACK SOFT CLAY 2 20 BROWN SOFT CLAY 20 85 BLUE SOFT SAND + GRAVEL 85 93 BROWN SOFT CLAY 93 130 BROWN MEDIUM SAND 130 165 BROWN HARD						Well Hydrofractured? Yes ☐ No ☒ From To		
						Casing Type Single casing ☐ Joint ☐		
						Drive Shoe? Yes ☐ No ☐ Above/Below		
						Casing Diameter 5 in. To 160 ft. 0 lbs./ft.		
						Hole Diameter 9 in. To 160 ft.		
						Open Hole From ft. To ft.		
						Screen? ☒ Type telescoping Make JOHNSON		
						Diameter Slot/Gauze Length Set		
						5 in. 15 10 ft. 150 ft. 160 ft.		
						Static Water Level 70 ft. land surface Measure 11/05/2025		
Pumping Level (below land surface) 75 ft. 3 hrs. Pumping at 25 g.p.m.								
Wellhead Completion Pitless adapter manufacturer MIDWEST Model MAAS ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 15 Sacks ft. 120 ft.								
Nearest Known Source of Contamination 140 feet North Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed 11/06/2025 Manufacturer's name GRUNDFOS Model Number 22SQE HP 1.5 Volt 220 Length of drop pipe 120 ft Capacity 22 g.p. Typ Submersible								
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No								
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-brown Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 390549 Y 4832214 Unique Number Verification Address verification Input Date 03/09/2026								
Angled Drill Hole								
Well Contractor Jerrys Well Service, Inc. 1462 ANDERSON, N Licensee Business Lic. or Reg. No. Name of Driller								