

865187

County

Stevens

Quad

Quad ID

MINNESOTA DEPARTMENT OF HEALTH

WELL AND BORING REPORT

Minnesota Statutes Chapter 1031

Entry Date05/11/2026

Update Date05/11/2026

Received Date11/03/2025

Well NameTownshipRangeDir SectionSubsection NOHL, GARY12341W 10null					Well DepthDepth CompletedDate Well Completed 82 ft.82 ft.10/10/2025																																
ElevationElev. Method					Drill MethodNon-specified RotaryDrill FluidBentonite																																
Address Well29250 1 CR HANCOCK MN Contact43556 280TH ST HANCOCK MN 56244					Use domesticStatusActive																																
Stratigraphy Information <table><thead><tr><th>Geological Material</th><th>From</th><th>To (ft.)</th><th>Color</th><th>Hardness</th></tr></thead><tbody><tr><td>TOP SOIL</td><td>0</td><td>3</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>3</td><td>18</td><td>YELLOW</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>18</td><td>48</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>48</td><td>65</td><td>GRAY</td><td>HARD</td></tr><tr><td>SAND</td><td>65</td><td>82</td><td>GRAY</td><td>SOFT</td></tr></tbody></table>					Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	3	BLACK	SOFT	CLAY	3	18	YELLOW	MEDIUM	CLAY	18	48	GRAY	MEDIUM	CLAY	48	65	GRAY	HARD	SAND	65	82	GRAY	SOFT	Well Hydrofractured?YesNoFromTo Casing TypeSingle casingJoint Drive Shoe?YesNoAbove/Below Casing DiameterWeightHole Diameter 6 in. To 62 ft. lbs./ft.9 in. To 82 ft.		
Geological Material	From	To (ft.)	Color	Hardness																																	
TOP SOIL	0	3	BLACK	SOFT																																	
CLAY	3	18	YELLOW	MEDIUM																																	
CLAY	18	48	GRAY	MEDIUM																																	
CLAY	48	65	GRAY	HARD																																	
SAND	65	82	GRAY	SOFT																																	
					Open HoleFromft.Toft. Screen?Type telescopingMakeJOHNSON DiameterSlot/GauzeLengthSet 6 in. 1510 ft. 72 ft. 82 ft.																																
					Static Water Level 19 ft. land surfaceMeasure10/11/2025																																
					Pumping Level (below land surface) ft.hrs.Pumping atg.p.m.																																
					Wellhead Completion Pitless adapter manufacturerMERRILLModelMCK-612 Casing Protection12 in. above grade At-grade (Environmental Wells and Borings ONLY)																																
					Grouting InformationWell Grouted?YesNoNot Specified MaterialAmountFromTo high solids bentonite6 Sacksft. 64 ft.																																
					Nearest Known Source of Contamination 70 feetWest DirectionSeptic tank/drain field Type Well disinfected upon completion?YesNo																																
					PumpNot InstalledDate Installed Manufacturer's name Model NumberHPVolt Length of drop pipeftCapacityg.p.Type																																
					Abandoned Does property have any not in use and not sealed well(s)?YesNo																																
					Variance Was a variance granted from the MDH for this well?YesNo																																
					Miscellaneous First BedrockAquifer Last StratDepth to Bedrockft Located by Locate Method SystemUTM - NAD83, Zone 15, MetersXY Unique Number VerificationInput Date																																
					Angled Drill Hole																																
					Well Contractor Conroy Well Drilling, Inc.1987CONROY, J Licensee BusinessLic. or Reg. No.Name of Driller																																