

866746

County McLeod
Quad Hutchinson
Quad ID 108B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 01/03/2024
Update Date 06/12/2025
Received Date 09/10/2024

Well Name SIMONSON, Elevation 1096 Address Well 19282 210TH ST HUTCHINSON MN Contact 1212 NEW HALL DR FARIBAULT MN Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>2</td><td>BLACK</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>2</td><td>24</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>24</td><td>128</td><td>GRAY</td><td>HARD</td></tr><tr><td>WATER/GRAVEL</td><td>128</td><td>138</td><td>VARIED</td><td>SOFT</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	2	BLACK	MEDIUM	CLAY	2	24	BROWN	MEDIUM	CLAY	24	128	GRAY	HARD	WATER/GRAVEL	128	138	VARIED	SOFT	Well Depth 138 ft. Drill Method Non-specified Rotary Use domestic Well Hydrofractured? Yes ☐ No ☒ Casing Type Single casing Drive Shoe? Yes ☐ No ☐ Casing Diameter 4 in. To 134 ft. Weight lbs./ft. Hole Diameter 8 in. To 138 ft. Open Hole From ft. To ft. Screen? ☒ Type stainless Make JOHNSON <table><tr><td>Diameter</td><td>Slot/Gauze</td><td>Length</td><td>Set</td></tr><tr><td>4 in.</td><td>15</td><td>4 ft.</td><td>134 ft.</td></tr></table> Static Water Level 34 ft. land surface Measure 09/11/2023 Pumping Level (below land surface) 8 ft. 1 hrs. Pumping at 50 g.p.m. Wellhead Completion Pitless adapter manufacturer BAKER Model PS54S4C0 ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified <table><tr><td>Material</td><td>Amount</td><td>From</td><td>To</td></tr><tr><td>cuttings</td><td></td><td>1 ft.</td><td>50 ft.</td></tr><tr><td>bentonite</td><td>4 Sacks</td><td></td><td>ft. 50 ft.</td></tr></table> Nearest Known Source of Contamination 50 feet Northwes Direction Well disinfected upon completion? ☐ Yes ☐ No Pump ☐ Not Installed Date Installed 09/28/2023 Manufacturer's name FLOWISE Model Number P18S10 HP 1 Volt 230 Length of drop pipe 80 ft Capacity 18 g.p. Typ Submersible Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Minnesota Department of Health Locate Method GPS SA Off (averaged) (15 meters) System UTM - NAD83, Zone 15, Meters X 390649 Y 4975361 Unique Number Verification Info/GPS from data Input Date 01/03/2024 Angled Drill Hole Well Contractor LTP Enterprises, Inc. 2157 SCHULTZ, N Licensee Business Lic. or Reg. No. Name of Driller		Diameter	Slot/Gauze	Length	Set	4 in.	15	4 ft.	134 ft.	Material	Amount	From	To	cuttings		1 ft.	50 ft.	bentonite	4 Sacks		ft. 50 ft.
Geological Material	From	To (ft.)	Color	Hardness																																															
TOP SOIL	0	2	BLACK	MEDIUM																																															
CLAY	2	24	BROWN	MEDIUM																																															
CLAY	24	128	GRAY	HARD																																															
WATER/GRAVEL	128	138	VARIED	SOFT																																															
Diameter	Slot/Gauze	Length	Set																																																
4 in.	15	4 ft.	134 ft.																																																
Material	Amount	From	To																																																
cuttings		1 ft.	50 ft.																																																
bentonite	4 Sacks		ft. 50 ft.																																																
Minnesota Well Index Report		866746	Printed on 08/13/2026 HE-01205-15																																																