

868954

County Hubbard
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 01/12/2024
Update Date 01/12/2024
Received Date 10/30/2023

Well Name ROGER	Township 141	Range 35	Dir Section W 9	Subsection CAA	Well Depth 77 ft.	Depth Completed 77 ft.	Date Well Completed 09/16/2023
Elevation	Elev. Method				Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address					Use domestic	Status Active	
Contact 27243 48 CH OSAGE MN 56570					Well Hydrofractured? Yes ☐ No ☒ From To		
Well 26466 ISLAND MICHELLE LEE TR PARK RAPIDS MN					Casing Type Single casing Joint Unknown		
Stratigraphy Information					Drive Shoe? Yes ☐ No ☒ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter	
TOP SOIL		0	1	BLACK	SOFT	4 in. To 72 ft. 1 lbs./ft. 6.7 in. To 77 ft.	
SANDY CLAY		1	8	BROWN	SOFT		
SAND		8	40	BROWN	SOFT		
CLAY		40	61	GRAY	HARD		
SAND		61	77	GRAY	SOFT		
					Open Hole From ft. To ft.		
					Screen? ☒ Type plastic Make BRADY		
					Diameter Slot/Gauze Length Set		
					4 in. 12 5 ft. 72 ft. 77 ft.		
					Static Water Level		
					25 ft. land surface Measure 09/15/2023		
					Pumping Level (below land surface)		
					ft. hrs. Pumping at g.p.m.		
					Wellhead Completion		
					Pitless adapter manufacturer MONITOR Model SNAPPY		
					☐ Casing Protection ☒ 12 in. above grade		
					☐ At-grade (Environmental Wells and Borings ONLY)		
					Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
					Material Amount From To		
					high solids bentonite 5 Sacks ft. 50 ft.		
					Nearest Known Source of Contamination		
					50 feet West Direction Septic tank/drain field Type		
					Well disinfected upon completion? ☒ Yes ☐ No		
					Pump ☐ Not Installed Date Installed 10/08/2023		
					Manufacturer's name PENTEK		
					Model Number S10P4IP052 HP 0.5 Volt 230		
					Length of drop pipe 60 ft Capacity 10 g.p. Typ Submersible		
					Abandoned		
					Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No		
					Variance		
					Was a variance granted from the MDH for this well? ☐ Yes ☒ No		
					Miscellaneous		
					First Bedrock Aquifer		
					Last Strat Depth to Bedrock ft		
					Located by		
					Locate Method		
					System UTM - NAD83, Zone 15, Meters X Y		
					Unique Number Verification Input Date		
					Angled Drill Hole		
					Well Contractor		
					Elsner Well Drilling, Inc. 1374 ELSNER, K.		
					Licensee Business Lic. or Reg. No. Name of Driller		