

869476

County Beltrami
Quad Bemidji
Quad ID 302A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 10/07/2025
Received Date 11/21/2022

Well Name ANDERSON,	Township 146	Range 32	Dir Section W 32	Subsection CCBCCD	Well Depth 90 ft.	Depth Completed 85 ft.	Date Well Completed 10/14/2022
Elevation 1381	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Bentonite
Address C/W 5100 SUNNYSIDE RD SE BEMIDJI MN 56601					Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 34 BROWN MEDIUM SAND GRAVEL 34 79 BROWN SOFT SAND GRAVEL 79 90 GRAY SOFT					Well Hydrofractured? Yes ☐ No ☒ From To		
					Casing Type Single casing Joint		
					Drive Shoe? Yes ☐ No ☐ Above/Below		
					Casing Diameter Weight Hole Diameter		
					4 in. To 80 ft. lbs./ft. 7.9 in. To 20 ft.		
					6.7 in. To 90 ft.		
					Open Hole From ft. To ft.		
					Screen? ☒ Type stainless Make JOHNSON		
					Diameter Slot/Gauze Length Set		
					2 in. 12 5 ft. 80 ft. 85 ft.		
Static Water Level 41 ft. land surface Measure 10/14/2022							
Pumping Level (below land surface) 70 ft. 1 hrs. Pumping at 10 g.p.m.							
Wellhead Completion Pitless adapter manufacturer MERRILL Model MCK40 ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)							
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To other 5 Sacks ft. 50 ft.							
Nearest Known Source of Contamination 53 feet South Direction Sewer Type Well disinfected upon completion? ☐ Yes ☐ No							
Pump ☐ Not Installed Date Installed 10/17/2022 Manufacturer's name GRUNDFOS Model Number SQ200-07 HP 0.75 Volt 230 Length of drop pipe 78 ft Capacity 10 g.p. Typ Submersible							
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No							
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand +larger-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 365924 Y 525489 Unique Number Verification Address verification Input Date 10/01/2025							
Angled Drill Hole							
Well Contractor Gracco Well Drilling 2960 CESOLINI, C. Licensee Business Lic. or Reg. No. Name of Driller							

Remarks