

872617

County Scott
Quad Veseli
Quad ID 89C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/09/2024
Update Date 08/13/2025
Received Date 08/30/2023

Well Name SKLUZACEK,	Township 113	Range 22	Dir Section W 33	Subsection DCABBD	Well Depth 238 ft.	Depth Completed 237 ft.	Date Well Completed 08/01/2023
Elevation 1007.2	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Water
Address C/W 2650 E 280TH ST NEW PRAGUE MN 56021					Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness CLAY 0 22 BROWN SOFT CLAY 22 108 GRAY SOFT SANDY CLAY 108 138 GRAY MEDIUM CLAY 138 181 GRAY MEDIUM SAND & CLAY 181 222 GRAY SOFT SAND 222 238 BROWN SOFT					Well Hydrofractured? Yes ☐ No ☒ From To		
					Casing Type Single casing Joint Welded		
					Drive Shoe? Yes ☐ No ☒ Above/Below		
					Casing Diameter 4 in. Weight 227 lbs./ft. Hole Diameter 6.5 in. To 238 ft.		
					Open Hole From ft. To ft.		
					Screen? ☒ Type plastic Make MONO FLEX		
					Diameter Slot/Gauze Length Set 4 in. 15 10 ft. 227 ft. 237 ft.		
					Static Water Level 61 ft. land surface Measure 07/31/2023		
					Pumping Level (below land surface) ft. hrs. Pumping at g.p.m.		
					Wellhead Completion Pitless adapter manufacturer MONITOR Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)		
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 2 Sacks ft. 50 ft.							
Nearest Known Source of Contamination 64 feet East Direction Tanks Type Well disinfected upon completion? ☒ Yes ☐ No							
Pump ☐ Not Installed Date Installed 08/01/2023 Manufacturer's name GRUNDFOS Model Number 22SQE15- HP 1.5 Volt 230 Length of drop pipe 100 ft Capacity 22 g.p. Typ Submersible							
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No							
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No							
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 462794 Y 4932725 Unique Number Verification Info/GPS from data Input Date 08/13/2025							
Angled Drill Hole							
Well Contractor Hartmann Well Co., LLP 1622 HARTMANN, B Licensee Business Lic. or Reg. No. Name of Driller							