

879224

County Murray
Quad Currie
Quad ID 62C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 01/12/2026
Update Date 01/12/2026
Received Date 12/15/2025

Well Name Township Range Dir Section Subsection GERVAIS, J&D 107 40 W 4 DDDBCD					Well Depth 167 ft.		Depth Completed 167 ft.		Date Well Completed 11/25/2025	
Elevation 1572 Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary		Drill Fluid			
Address C/W 2090 171ST ST CURRIE MN 56123					Use domestic		Status Active			
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOP SOIL 0 3 BLACK HARD CLAY 3 29 YELLOW HARD CLAY 29 77 GRAY HARD SAND 77 79 GRAY SOFT CLAY 79 107 YELLOW HARD SANDY-CLAY 107 112 YELLOW SOFT LENSES SAND 112 124 YELLOW SOFT SAND 124 128 YELLOW SOFT CLAY 128 150 GRAY HARD SAND 150 153 GRAY HARD GRAVEL 153 166 GRAY HARD CLAY 166 167 GRAY HARD					Well Hydrofractured? Yes ☐ No ☐ From To					
					Casing Type Single casing Joint					
					Drive Shoe? Yes ☐ No ☐ Above/Below					
					Casing Diameter Weight 5 in. To 157 ft. lbs./ft.					
					Open Hole From ft. To ft.					
					Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 5 in. 30 10 ft. 157 ft. 167 ft.					
					Static Water Level 120 ft. land surface Measure 11/25/2025					
					Pumping Level (below land surface) 145 ft. 2 hrs. Pumping at 25 g.p.m.					
					Wellhead Completion Pitless adapter manufacturer MONITOR Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)					
					Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 12 Sacks ft. 150 ft.					
Nearest Known Source of Contamination <u>150</u> feet <u>Northwes</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☐ Yes ☐ No										
Pump ☐ Not Installed Date Installed <u>11/25/2025</u> Manufacturer's name GOULDS Model Number <u>18GS20</u> HP <u>2</u> Volt <u>230</u> Length of drop pipe <u>140</u> ft Capacity <u>20</u> g.p. Typ <u>Submersible</u>										
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No										
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No										
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat clay-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 288270 Y 4885909 Unique Number Verification Address verification Input Date 01/12/2026										
Angled Drill Hole										
Well Contractor Spartz and Sons Well Co. 1413 SPARTZ, T. Licensee Business Lic. or Reg. No. Name of Driller										