

879367

County St. Louis
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/06/2026
Update Date 04/06/2026
Received Date 12/22/2025

Well Name MIDAS, MARK					Township 59	Range 20	Dir Section W 29	Subsection ADD	Well Depth 224 ft.		Depth Completed 224 ft.		Date Well Completed 10/21/2025																																
Elevation					Elev. Method					Drill Method Multiple methods used		Drill Fluid																																	
Address C/W 6229 BALSH RD CHISHOLM MN 55719									Use domestic		Status Active																																		
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>5</td><td>TAN</td><td>SOFT</td></tr><tr><td>SAND</td><td>5</td><td>7</td><td>BROWN</td><td>SOFT</td></tr><tr><td>ROCKS</td><td>7</td><td>8</td><td>VARIED</td><td>HARD</td></tr><tr><td>SAND</td><td>8</td><td>18</td><td>BROWN</td><td>SOFT</td></tr><tr><td>ROCKS</td><td>18</td><td>23</td><td>VARIED</td><td>HARD</td></tr><tr><td>GRANITE</td><td>23</td><td>224</td><td>RED</td><td>HARD</td></tr></table>									Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	5	TAN	SOFT	SAND	5	7	BROWN	SOFT	ROCKS	7	8	VARIED	HARD	SAND	8	18	BROWN	SOFT	ROCKS	18	23	VARIED	HARD	GRANITE	23	224	RED	HARD	Well Hydrofractured? Yes ☐ No ☒ From To	
									Geological Material	From	To (ft.)	Color	Hardness																																
									CLAY	0	5	TAN	SOFT																																
									SAND	5	7	BROWN	SOFT																																
									ROCKS	7	8	VARIED	HARD																																
									SAND	8	18	BROWN	SOFT																																
									ROCKS	18	23	VARIED	HARD																																
									GRANITE	23	224	RED	HARD																																
									Casing Type Single casing		Joint Threaded																																		
									Drive Shoe? Yes ☒ No ☐		Above/Below																																		
Casing Diameter 6 in. To 23 ft.		Weight lbs./ft.		Hole Diameter 10 in. To 23 ft. 6 in. To 224 ft.																																									
Open Hole From 23 ft. To 224 ft.																																													
Screen? ☐		Type		Make																																									
Static Water Level 22 ft. land surface Measure 10/21/2025																																													
Pumping Level (below land surface) ft. hrs. Pumping at 4 g.p.m.																																													
Wellhead Completion Pitless adapter manufacturer SNAPPY Model 4C-1 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																													
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 2 Sacks ft. 23 ft.																																													
Nearest Known Source of Contamination <u>100</u> feet <u>North</u> Direction <u>Sewer</u> Type Well disinfected upon completion? ☐ Yes ☐ No																																													
Pump ☐ Not Installed Date Installed Manufacturer's name STA-RITE Model Number <u>HS</u> HP <u>0.75</u> Volt <u>230</u> Length of drop pipe <u>200</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>																																													
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																													
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																													
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																													
Angled Drill Hole																																													
Well Contractor Marks Well and Pump 1675 SWADER, M Licensee Business Lic. or Reg. No. Name of Driller																																													