

880096

County Itasca
Quad La Prairie
Quad ID 272B

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 10/15/2025
Received Date 09/19/2024

Well Name ZIMMER	Township 55	Range 25	Dir W	Section 35	Subsection CBCACB	Well Depth 72 ft.	Depth Completed 72 ft.	Date Well Completed 07/25/2024																																								
Elevation 1315.6	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid																																									
Address C/W 4295 DAVIS RD GRAND RAPIDS MN 55744						Use domestic	Status Active																																									
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>2</td><td>BLACK</td><td>HARD</td></tr><tr><td>SAND</td><td>2</td><td>12</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY SAND</td><td>12</td><td>40</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND</td><td>40</td><td>48</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY SAND</td><td>48</td><td>60</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND</td><td>60</td><td>64</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND</td><td>64</td><td>72</td><td>BLUE</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	2	BLACK	HARD	SAND	2	12	BROWN	SOFT	CLAY SAND	12	40	BROWN	SOFT	SAND	40	48	BROWN	SOFT	CLAY SAND	48	60	BROWN	SOFT	SAND	60	64	BROWN	SOFT	SAND	64	72	BLUE	SOFT	Well Hydrofractured? Yes ☐ No ☒ From To		
						Geological Material	From	To (ft.)	Color	Hardness																																						
						TOP SOIL	0	2	BLACK	HARD																																						
						SAND	2	12	BROWN	SOFT																																						
						CLAY SAND	12	40	BROWN	SOFT																																						
						SAND	40	48	BROWN	SOFT																																						
						CLAY SAND	48	60	BROWN	SOFT																																						
						SAND	60	64	BROWN	SOFT																																						
						SAND	64	72	BLUE	SOFT																																						
						Casing Type Single casing ☐ Joint ☐																																										
Drive Shoe? Yes ☐ No ☒ Above/Below																																																
Casing Diameter 4 in. To 64 ft. 2.25 lbs./ft.																																																
Weight 7.9 in. To 72 ft.																																																
Hole Diameter																																																
Open Hole From ft. To ft.																																																
Screen? ☒ Type stainless Make JOHNSON																																																
Diameter 4 in. Slot/Gauze 7 Length 8 ft. Set 64 ft. 72 ft.																																																
Static Water Level 28 ft. land surface Measure 07/25/2024																																																
Pumping Level (below land surface) 60 ft. 2 hrs. Pumping at 30 g.p.m.																																																
Wellhead Completion Pitless adapter manufacturer AQUA SEAL Model T-SERIES ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 6 Sacks ft. 50 ft.																																																
Nearest Known Source of Contamination 55 feet West Direction Sewer Type Well disinfected upon completion? ☒ Yes ☐ No																																																
Pump ☐ Not Installed Date Installed 09/13/2024 Manufacturer's name STA-RITE Model Number S10P4HS05 HP 0.5 Volt 115 Length of drop pipe 50.1 ft Capacity 10 g.p. Typ Submersible																																																
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No																																																
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																																
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 462930 Y 5227575 Unique Number Verification Address verification Input Date 10/15/2025																																																
Angled Drill Hole																																																
Well Contractor Benes Well Drilling, Inc. 1542 BENES, D Licensee Business Lic. or Reg. No. Name of Driller																																																