

880579

County Beltrami
Quad Nebish
Quad ID 359D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/25/2025
Update Date 06/17/2025
Received Date 10/25/2024

Well Name REIS. PAUL	Township 149	Range 32	Dir W	Section 5	Subsection ABAACA
Elevation 1368	Elev. Method LiDAR 1m DEM (MNDNR)				
Address C/W 7948 NEBISH RD NE TENSTRIKE MN 56683					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
CLAY		0	27	YELLOW	MEDIUM
CLAY		27	96	GRAY	MEDIUM
SAND		96	102	VARIED	SOFT
Well Depth 102 ft.		Depth Completed 102 ft.		Date Well Completed 06/13/2024	
Drill Method Non-specified Rotary		Drill Fluid			
Use domestic				Status Active	
Well Hydrofractured?		Yes ☐	No ☒	From	To
Casing Type Single casing		Joint			
Drive Shoe?		Yes ☐	No ☐	Above/Below	
Casing Diameter 4 in. To		Weight 98 ft. 1.87 lbs./ft.		Hole Diameter 8 in. To 50 ft. 6.5 in. To 102 ft.	
Open Hole		From	ft.	To	ft.
Screen? ☒		Type stainless		Make JOHNSON	
Diameter 2 in.		Slot/Gauze 10	Length 4 ft.	Set 98 ft.	102 ft.
Static Water Level 42 ft. land surface Measure 06/13/2024					
Pumping Level (below land surface) 102 ft. 1 hrs. Pumping at 25 g.p.m.					
Wellhead Completion					
Pitless adapter manufacturer		AQUA SEAL		Model T SER	
☐ Casing Protection		☐ 12 in. above grade			
☐ At-grade (Environmental Wells and Borings ONLY)					
Grouting Information		Well Grouted? ☒ Yes ☐ No ☐ Not Specified			
Material high solids bentonite		Amount 3 Sacks		From	To ft. 50 ft.
Nearest Known Source of Contamination					
65 feet		West Direction		Sewer Type	
Well disinfected upon completion?		☐ Yes ☐ No			
Pump ☐ Not Installed		Date Installed		06/13/2024	
Manufacturer's name		GOULDS			
Model Number		10CS05	HP	0.5	Volt 230
Length of drop pipe		80 ft	Capacity	18 g.p.	Typ Submersible
Abandoned					
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No					
Variance					
Was a variance granted from the MDH for this well? ☐ Yes ☒ No					
Miscellaneous					
First Bedrock		Aquifer		Quat. buried	
Last Strat		sand		Depth to Bedrock ft	
Located by		Minnesota Geological Survey			
Locate Method		Digitization (Screen) - Map (1:24,000) (15 meters or			
System		UTM - NAD83, Zone 15, Meters		X 367428	Y 5290990
Unique Number Verification		Address verification		Input Date	06/17/2025
Angled Drill Hole					
Well Contractor					
Bradseth Well Drilling		2134		BRADSETH. C	
Licensee Business		Lic. or Reg. No.		Name of Driller	