

881778

County Martin
Quad Welcome
Quad ID 15A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 08/12/2025
Received Date 06/20/2025

Well Name REDENINS,	Township 102	Range 31	Dir W	Section 11	Subsection DCDDAD	Well Depth 134 ft.	Depth Completed 134 ft.	Date Well Completed 06/06/2025
Elevation 1234	Elev. Method LiDAR 1m DEM (MNDNR)				Drill Method Non-specified Rotary	Drill Fluid Qwik gel		
Address C/W 1776 110TH ST FAIRMONT MN 56031						Use domestic	Status Active	
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOP SOIL 0 2 BLACK SOFT CLAY 2 24 YELLOW SOFT CLAY/ SANDY 24 121 GRAY MEDIUM SAND 121 134 VARIED SOFT						Well Hydrofractured? Yes ☐ No ☒ From To		
						Casing Type Single casing Joint		
						Drive Shoe? Yes ☐ No ☒ Above/Below		
						Casing Diameter 5 in. To 124 ft. 0 lbs./ft.		
						Hole Diameter 9 in. To 134 ft.		
						Open Hole From ft. To ft.		
						Screen? ☒ Type stainless Make JOHNSON		
						Diameter Slot/Gauze Length Set		
						4 in. 20 10 ft. 124 ft. 134 ft.		
						Static Water Level 90 ft. land surface Measure 06/06/2025		
Pumping Level (below land surface) 120 ft. 3 hrs. Pumping at 14 g.p.m.								
Wellhead Completion Pitless adapter manufacturer MAAS Model 5JC1 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 4 Sacks ft. 124 ft.								
Nearest Known Source of Contamination 60 feet West Direction Old/other well Type Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed 06/10/2025 Manufacturer's name FLINT & WALLING Model Number 10S07-8 HP 0.75 Volt 230 Length of drop pipe 120 ft Capacity 10 g.p. Typ Submersible								
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No								
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No								
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 377605 Y 4833653 Unique Number Verification Address verification Input Date 08/12/2025								
Angled Drill Hole								
Well Contractor Beemer Well Drilling, Inc. 1494 HATFIELD, T Licensee Business Lic. or Reg. No. Name of Driller								