

882864

County Wright
Quad Cokato
Quad ID 123C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 10/21/2025
Update Date 11/03/2025
Received Date 01/28/2025

Well Name MATTTILA, Elevation 994.1 Address Well 13358 25TH ST SW COKATO MN 55321 Contact COKATO MN 55321 Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>20</td><td>YELLOW</td><td></td></tr><tr><td>SAND ROCKS</td><td>20</td><td>67</td><td>YELLOW</td><td></td></tr><tr><td>SAND</td><td>67</td><td>77</td><td></td><td></td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	20	YELLOW		SAND ROCKS	20	67	YELLOW		SAND	67	77			Well Depth 77 ft. Drill Method Non-specified Rotary Use domestic Well Hydrofractured? Yes ☐ No ☒ Casing Type Single casing Drive Shoe? Yes ☐ No ☒ Casing Diameter 4 in. To 73 ft. Weight lbs./ft. Hole Diameter 6.7 in. To 77 ft. Open Hole From ft. To ft. Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 3 in. 12 4 ft. 73 ft. 77 ft. Static Water Level 30 ft. land surface Measure 07/11/2024 Pumping Level (below land surface) 40 ft. 1 hrs. Pumping at 40 g.p.m. Wellhead Completion Pitless adapter manufacturer Model BULLDOG ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 3 Sacks 6 ft. 50 ft. Nearest Known Source of Contamination 80 feet South Direction Sewer Type Well disinfected upon completion? ☒ Yes ☐ No Pump ☐ Not Installed Date Installed 07/12/2024 Manufacturer's name FLOWISE Model Number P10S05 HP 0.5 Volt 230 Length of drop pipe 60 ft Capacity 10 g.p. Typ Submersible Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 408662 Y 4996895 Unique Number Verification Info/GPS from data Input Date 11/03/2025 Angled Drill Hole Well Contractor Mattson Well Co. 1544 MILLER, J Licensee Business Lic. or Reg. No. Name of Driller				
Geological Material	From	To (ft.)	Color	Hardness																									
CLAY	0	20	YELLOW																										
SAND ROCKS	20	67	YELLOW																										
SAND	67	77																											
Minnesota Well Index Report					882864		Printed on 08/13/2026 HE-01205-15																						