

883532

County Hennepin
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 02/17/2026
Received Date 11/17/2025

Well Name GORDON JAMES	Township 118	Range 23	Dir W	Section 24	Subsection DAA																									
Elevation Elev. Method																														
Address Well 1650 ORCHARD CHEEL TR ORONO MN 55356 Contact PO BOX 306 MAPLE PLAIN MN 55359																														
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>10</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>10</td><td>127</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>127</td><td>136</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND</td><td>136</td><td>146</td><td>VARIED</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	10	BLACK	SOFT	CLAY	10	127	GRAY	SOFT	CLAY	127	136	BROWN	SOFT	SAND	136	146	VARIED	SOFT
Geological Material	From	To (ft.)	Color	Hardness																										
CLAY	0	10	BLACK	SOFT																										
CLAY	10	127	GRAY	SOFT																										
CLAY	127	136	BROWN	SOFT																										
SAND	136	146	VARIED	SOFT																										
Well Depth 146 ft. Depth Completed 146 ft. Date Well Completed 11/05/2025																														
Drill Method Non-specified Rotary Drill Fluid Bentonite																														
Use domestic Status Active																														
Well Hydrofractured? Yes ☐ No ☒ From To																														
Casing Type Single casing Joint																														
Drive Shoe? Yes ☐ No ☐ Above/Below																														
Casing Diameter 4 in. Weight 136 ft. lbs./ft. Hole Diameter 7.8 in. To 50 ft. 6.5 in. To 146 ft.																														
Open Hole From ft. To ft.																														
Screen? ☒ Type other Make Diameter Slot/Gauze Length Set 4 in. 0 10 ft. 136 ft. 146 ft.																														
Static Water Level 44 ft. land surface Measure 06/25/2025																														
Pumping Level (below land surface) 80 ft. 3 hrs. Pumping at 40 g.p.m.																														
Wellhead Completion Pitless adapter manufacturer BAKER Model MONITOR ☐ Casing Protection ☒ 12 in. above grade ☒ At-grade (Environmental Wells and Borings ONLY)																														
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To cuttings 50 ft. 136 ft. bentonite 5 Sacks ft. 50 ft.																														
Nearest Known Source of Contamination 50 feet West Direction Other Type Well disinfected upon completion? ☒ Yes ☐ No																														
Pump ☐ Not Installed Date Installed 11/05/2025 Manufacturer's name FRANKLIN Model Number EPS4400 HP 1.5 Volt 230 Length of drop pipe 80 ft Capacity 20 g.p. Typ Submersible																														
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																														
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																														
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																														
Angled Drill Hole																														
Well Contractor Bergerson Caswell, Inc. 1767 SCHWARTZ, M Licensee Business Lic. or Reg. No. Name of Driller																														