

883550

County Hennepin
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 04/08/2026
Update Date 04/08/2026
Received Date 07/14/2025

Well Name COTE, NATE	Township 120	Range 23	Dir Section W 27	Subsection DBC	Well Depth 184 ft.	Depth Completed 184 ft.	Date Well Completed 06/24/2025																																			
Elevation	Elev. Method				Drill Method Non-specified Rotary	Drill Fluid Bentonite																																				
Address C/W 23300 SADLE RIDGE DR MN					Use domestic	Status Active																																				
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>45</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND, GRAVEL</td><td>45</td><td>85</td><td>VARIED</td><td>SOFT</td></tr><tr><td>CLAY, GRAVEL</td><td>85</td><td>150</td><td>BROWN</td><td>SOFT</td></tr><tr><td>GRAVEL</td><td>150</td><td>153</td><td>VARIED</td><td>SOFT</td></tr><tr><td>CLAY, GRAVEL</td><td>153</td><td>172</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND, GRAVEL</td><td>172</td><td>184</td><td>VARIED</td><td>MEDIUM</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	45	BROWN	SOFT	SAND, GRAVEL	45	85	VARIED	SOFT	CLAY, GRAVEL	85	150	BROWN	SOFT	GRAVEL	150	153	VARIED	SOFT	CLAY, GRAVEL	153	172	GRAY	MEDIUM	SAND, GRAVEL	172	184	VARIED	MEDIUM	Well Hydrofractured? Yes ☐ No ☐ From To		
					Geological Material	From	To (ft.)	Color	Hardness																																	
					CLAY	0	45	BROWN	SOFT																																	
					SAND, GRAVEL	45	85	VARIED	SOFT																																	
					CLAY, GRAVEL	85	150	BROWN	SOFT																																	
					GRAVEL	150	153	VARIED	SOFT																																	
					CLAY, GRAVEL	153	172	GRAY	MEDIUM																																	
					SAND, GRAVEL	172	184	VARIED	MEDIUM																																	
					Casing Type Single casing ☐ Joint ☐																																					
					Drive Shoe? Yes ☐ No ☒ Above/Below																																					
Hole Diameter 7.8 in. To 50 ft. 6.5 in. To 184 ft.																																										
Open Hole From ft. To ft.																																										
Screen? ☒ Type other Make Diameter Slot/Gauze Length Set 4 in. 0 10 ft. 174 ft. 184 ft.																																										
Static Water Level -48 ft. land surface Measure 06/24/2025																																										
Pumping Level (below land surface) 70 ft. 2 hrs. Pumping at 40 g.p.m.																																										
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																										
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To cuttings 50 ft. 174 ft. other 4 Sacks ft. 50 ft.																																										
Nearest Known Source of Contamination 30 feet North Direction Sewer Type Well disinfected upon completion? ☐ Yes ☐ No																																										
Pump ☐ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																																										
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																										
Variance Was a variance granted from the MDH for this well? ☐ Yes ☐ No																																										
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																										
Angled Drill Hole																																										
Well Contractor Bergerson Caswell, Inc. 1767 SCHWARTZ, M Licensee Business Lic. or Reg. No. Name of Driller																																										

Remarks