

884303

County Swift
Quad De Graff
Quad ID 144C

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 07/02/2026
Received Date 05/28/2025

Well Name BENSON,	Township 121	Range 37	Dir W	Section 7	Subsection BCBCDD
Elevation 1132	Elev. Method LiDAR 1m DEM (MNDNR)				
Address					
Contact 1155 12 HY SE MURDOCK MN 56271					
Well 135 120TH AV SE MURDOCK MN 56271					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
CLAY		0	25	YELLOW	
GRAVEL		25	33	BROWN	
CLAY		33	155	BLUE	MEDIUM
SAND		155	170	GRAY	MEDIUM

Well Depth 170 ft.	Depth Completed 170 ft.	Date Well Completed 05/13/2025			
Drill Method Non-specified Rotary	Drill Fluid Bentonite				
Use domestic	Status Active				
Well Hydrofractured? Yes ☐ No ☐		From To			
Casing Type Single casing		Joint			
Drive Shoe? Yes ☐ No ☐		Above/Below			
Casing Diameter 4 in. To		Weight 162 ft. lbs./ft.		Hole Diameter 8.5 in. To 22 ft. 7.5 in. To 130 ft.	
Open Hole From ft. To ft.					
Screen? ☒		Type stainless		Make JOHNSON	
Diameter 4 in.		Slot/Gauze 15		Length 8 ft.	
				Set 162 ft.	
				170 ft.	
Static Water Level 30 ft. land surface Measure 05/13/2025					
Pumping Level (below land surface) 160 ft. 2 hrs. Pumping at 15 g.p.m.					
Wellhead Completion Pitless adapter manufacturer MERRILL Model SPK ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 50 ft. ft.					
Nearest Known Source of Contamination 75 feet Northwes Direction Sewer Type Well disinfected upon completion? ☐ Yes ☐ No					
Pump ☐ Not Installed Date Installed 05/14/2025 Manufacturer's name GRUNDFOS Model Number 22SQE1019 HP 1 Volt Length of drop pipe 100 ft Capacity g.p. Typ Submersible					
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No					
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No					
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 313659 Y 5019668 Unique Number Verification Address verification Input Date 07/02/2026					
Angled Drill Hole					
Well Contractor Dons Pump and Well Service 1451 MEULEBROECK, Licensee Business Lic. or Reg. No. Name of Driller					

Minnesota Well Index Report	884303	Printed on 08/13/2026 HE-01205-15
-----------------------------	--------	--------------------------------------