

884687

County Pine
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 01/06/2026
Update Date 01/06/2026
Received Date 04/30/2025

Well Name SMITH, BRIAN					Township 38	Range 22	Dir Section W 6	Subsection DBC	Well Depth 136 ft.		Depth Completed 136 ft.		Date Well Completed 10/03/2024																								
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Bentonite																									
Address C/W 10989 EAGLE LA GRASSTON MN 55030									Use domestic		Status Active																										
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>20</td><td>RED</td><td>MEDIUM</td></tr><tr><td>COARSE GRAVEL</td><td>20</td><td>110</td><td>VARIED</td><td>HARD</td></tr><tr><td>CLAY</td><td>110</td><td>120</td><td>RED</td><td>MEDIUM</td></tr><tr><td>SAND GRAVEL</td><td>120</td><td>136</td><td>BROWN</td><td>MEDIUM</td></tr></table>									Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	20	RED	MEDIUM	COARSE GRAVEL	20	110	VARIED	HARD	CLAY	110	120	RED	MEDIUM	SAND GRAVEL	120	136	BROWN	MEDIUM	Well Hydrofractured? Yes ☐ No ☒ From		To	
									Geological Material	From	To (ft.)	Color	Hardness																								
									CLAY	0	20	RED	MEDIUM																								
									COARSE GRAVEL	20	110	VARIED	HARD																								
									CLAY	110	120	RED	MEDIUM																								
									SAND GRAVEL	120	136	BROWN	MEDIUM																								
									Casing Type Single casing		Joint																										
									Drive Shoe? Yes ☐ No ☐		Above/Below																										
									Casing Diameter 4 in. To 132 ft.		Weight lbs./ft.																										
									Hole Diameter 8 in. To 50 ft.		6.7 in. To 136 ft.																										
Open Hole From ft. To ft.																																					
Screen? ☒ Type stainless		Make																																			
Diameter 3 in.		Slot/Gauze 20																																			
Length 4 ft.		Set ft.																																			
Static Water Level 16 ft. land surface		Measure 10/03/2024																																			
Pumping Level (below land surface) 130 ft. 2 hrs. Pumping at 12 g.p.m.																																					
Wellhead Completion Pitless adapter manufacturer BAKER Model SNAPPY ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 5 Sacks ft. 50 ft.																																					
Nearest Known Source of Contamination <u>60</u> feet <u>South</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No																																					
Pump ☐ Not Installed Date Installed Manufacturer's name GRUNDFOS Model Number HP 0.75 Volt 230 Length of drop pipe 60 ft Capacity 10 g.p. Typ Submersible																																					
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																					
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																					
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																					
Angled Drill Hole																																					
Well Contractor Sampson Well Co. 1863 SAMPSON, D Licensee Business Lic. or Reg. No. Name of Driller																																					