

884899

County Anoka
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 10/22/2025
Received Date 12/13/2024

Well Name SCHENDEL, TIM					Township 32	Range 23	Dir W	Section 6	Subsection ACC	Well Depth 135 ft.		Depth Completed 135 ft.		Date Well Completed 10/30/2024					
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Bentonite							
Address										Use domestic		Status Active							
C/W 715 176TH LA NE HAM LAKE MN 55304										Well Hydrofractured?		Yes ☐ No ☒		From		To			
Stratigraphy Information										Casing Type Single casing		Joint							
Geological Material										Drive Shoe?		Yes ☐ No ☒		Above/Below					
SAND										Casing Diameter		Weight		Hole Diameter					
CLAY										4 in. To		135 ft.		lbs./ft.		8 in. To 50 ft.			
CLAY																6.7 in. To 135 ft.			
CLAY																			
SAND																			
CLAY																			
SAND																			
										Open Hole		From		ft.		To		ft.	
										Screen? ☒		Type		other		Make		BIG FOOT	
										Diameter		Slot/Gauze		Length		Set			
										4 in.		8		15 ft.		118 ft.		132 ft.	
										Static Water Level									
										10 ft.		land surface				Measure		10/30/2024	
										Pumping Level (below land surface)									
										80 ft.		1 hrs.		Pumping at		50		g.p.m.	
										Wellhead Completion									
										Pitless adapter manufacturer		AQUASEAL		Model		4X1			
										☐ Casing Protection		☒ 12 in. above grade							
										☐ At-grade (Environmental Wells and Borings ONLY)									
										Grouting Information		Well Grouted?		☒ Yes ☐ No ☐ Not Specified					
										Material		Amount		From		To			
										bentonite		4 Sacks				ft. 50		ft.	
										Nearest Known Source of Contamination									
										50 feet		North		Direction				Other Type	
										Well disinfected upon completion?		☐ Yes ☐ No							
										Pump ☐ Not Installed		Date Installed		11/08/2024					
										Manufacturer's name		FLOWISE							
										Model Number		P10S05		HP 0.5		Volt 110			
										Length of drop pipe		40 ft		Capacity		g.p.		Typ Submersible	
										Abandoned									
										Does property have any not in use and not sealed well(s)?		☐ Yes ☐ No							
										Variance									
										Was a variance granted from the MDH for this well?		☐ Yes ☒ No							
										Miscellaneous									
										First Bedrock				Aquifer					
										Last Strat				Depth to Bedrock				ft	
										Located by									
										Locate Method									
										System		UTM - NAD83, Zone 15, Meters		X		Y			
										Unique Number Verification						Input Date			
										Angled Drill Hole									
										Well Contractor									
										Mork Well Co., Inc.		1877		RICKE, GREG					
										Licensee Business		Lic. or Reg. No.		Name of Driller					