

885099

County Washington
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date

Update Date12/31/2025

Received Date12/26/2024

Well Name GUIDENCE Elevation Address Well20859 INGERSON AV FOREST LAKE MN 55025 Contact167 LAKE ST FOREST LAKE MN 55025 Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND/ ROCKS</td><td>0</td><td>12</td><td>BROWN</td><td>HARD</td></tr><tr><td>CLAY</td><td>12</td><td>142</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND/ GRAVEL</td><td>142</td><td>152</td><td></td><td>SOFT</td></tr><tr><td>CLAY</td><td>152</td><td>161</td><td>GRAY</td><td></td></tr><tr><td>SAND/ GRAVEL</td><td>161</td><td>181</td><td></td><td>SOFT</td></tr></table>	Geological Material	From	To (ft.)	Color	Hardness	SAND/ ROCKS	0	12	BROWN	HARD	CLAY	12	142	GRAY	MEDIUM	SAND/ GRAVEL	142	152		SOFT	CLAY	152	161	GRAY		SAND/ GRAVEL	161	181		SOFT	Well Depth 181 ft. Drill Method Non-specified Rotary Use domestic Well Hydrofractured? Yes☐No☒ From To Casing Type Single casing Joint Drive Shoe? Yes☐No☐ Above/Below Casing Diameter Weight Hole Diameter 4 in. To171 ft. lbs./ft. 8 in. To50 ft. 6.5 in. To181 ft. Open Hole From ft. To ft. Screen? ☒ Type slotted Make Diameter Slot/Gauze Length Set in. 15 ft. 171 ft. 181 ft. Static Water Level Pumping Level (below land surface) 105 ft. 1 hrs. Pumping at 20 g.p.m. Wellhead Completion Pitless adapter manufacturer MONITOR Model SNAPPY ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY) Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 5 Sacks ft. 50 ft. Nearest Known Source of Contamination 65 feet West Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No Pump ☐ Not Installed Date Installed Manufacturer's name GRUNDFOS Model Number SQE HP 1 Volt 220 Length of drop pipe 80 ft Capacity 15 g.p. Typ Submersible Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date Angled Drill Hole Well Contractor Andy Zuercher Well Drilling 4697 ANDY III Licensee Business Lic. or Reg. No. Name of Driller
Geological Material	From	To (ft.)	Color	Hardness																											
SAND/ ROCKS	0	12	BROWN	HARD																											
CLAY	12	142	GRAY	MEDIUM																											
SAND/ GRAVEL	142	152		SOFT																											
CLAY	152	161	GRAY																												
SAND/ GRAVEL	161	181		SOFT																											