

885378

County Crow Wing
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 06/04/2025
Received Date 10/17/2024

Well Name ROKSER,	Township 45	Range 28	Dir W	Section 11	Subsection DAA	Well Depth 129 ft.	Depth Completed 129 ft.	Date Well Completed 09/26/2024
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Active	
Contact	2037 BIRCH ST WHITE BEAR LAKE MN 55110					Well Hydrofractured?	Yes ☐ No ☒	From To
Well	16430 BRIGHTON POINT RD DEERWOOD MN					Casing Type Single casing	Joint	
Stratigraphy Information						Drive Shoe?	Yes ☐ No ☐	Above/Below
Geological Material	From	To (ft.)	Color	Hardness	Casing Diameter	Weight	Hole Diameter	
CLAY	0	18	BROWN	MEDIUM	4 in. To	125 ft. lbs./ft.	6.5 in. To	129 ft.
SANDY CLAY	18	60	GRAY	MEDIUM				
SAND	60	92	BROWN	MEDIUM				
CLAY & GRAVEL	92	125	BROWN	MEDIUM				
SAND	125	129	BROWN	MEDIUM				
Open Hole								
Screen? ☒ Type stainless Make JOHNSON								
Diameter Slot/Gauze Length Set								
2 in. 10 4 ft. 125 ft. 129 ft.								
Static Water Level								
18 ft. land surface Measure 09/26/2024								
Pumping Level (below land surface)								
120 ft. 1 hrs. Pumping at 15 g.p.m.								
Wellhead Completion								
Pitless adapter manufacturer MONITOR Model SNAPPY								
☐ Casing Protection ☐ 12 in. above grade								
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information								
Well Grouted? ☒ Yes ☐ No ☐ Not Specified								
Material Amount From To								
bentonite 5 Sacks ft. 50 ft.								
Nearest Known Source of Contamination								
50 feet Direction Type								
Well disinfected upon completion? ☒ Yes ☐ No								
Pump ☐ Not Installed Date Installed								
Manufacturer's name STA-RITE								
Model Number HP 0.5 Volt 230								
Length of drop pipe 120 ft Capacity 10 g.p. Typ Submersible								
Abandoned								
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No								
Variance								
Was a variance granted from the MDH for this well? ☐ Yes ☒ No								
Miscellaneous								
First Bedrock Aquifer								
Last Strat Depth to Bedrock ft								
Located by								
Locate Method								
System UTM - NAD83, Zone 15, Meters X Y								
Unique Number Verification Input Date								
Angled Drill Hole								
Well Contractor								
Hasskamp Bros. Well Drilling 1585 CHAD & CORY								
Licensee Business Lic. or Reg. No. Name of Driller								