

885552

County Beltrami
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 01/15/2025
Update Date 01/15/2025
Received Date 11/12/2024

Well Name NOBAL, SHANE	Township 147	Range 34	Dir W	Section 27	Subsection CDD
Elevation	Elev. Method				
Address					
Well 4850TH 89 HY BEMIDJI MN 56601					
Contact 1702 PAUL BUNYOON DR NW BEMIDJI MN 56601					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
SAND		0	8	BROWN	SOFT
CLAY		8	52	GRAY	MEDIUM
SAND		52	62	GRAY	SOFT
Well Depth 62 ft. Depth Completed 62 ft. Date Well Completed 10/03/2024					
Drill Method Non-specified Rotary		Drill Fluid Bentonite			
Use domestic				Status Active	
Well Hydrofractured? Yes ☐ No ☒ From To					
Casing Type Single casing Joint					
Drive Shoe? Yes ☐ No ☒ Above/Below					
Casing Diameter		Weight		Hole Diameter	
4 in. To 54 ft.		lbs./ft.		8 in. To 62 ft.	
Open Hole From ft. To ft.					
Screen? ☒ Type stainless Make JOHNSON					
Diameter		Slot/Gauze		Length Set	
2 in.		10		8 ft. 54 ft. 62 ft.	
Static Water Level					
11 ft.		land surface		Measure 10/03/2024	
Pumping Level (below land surface)					
50 ft.		2 hrs.		Pumping at 35 g.p.m.	
Wellhead Completion					
Pitless adapter manufacturer		MONITOR		Model SNAPPY	
☐ Casing Protection		☒ 12 in. above grade			
☐ At-grade (Environmental Wells and Borings ONLY)					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified					
Material		Amount		From To	
bentonite		4 Sacks		ft. 50 ft.	
Nearest Known Source of Contamination					
80 feet		North Direction		Septic tank/drain field Type	
Well disinfected upon completion? ☒ Yes ☐ No					
Pump ☐ Not Installed Date Installed 10/03/2024					
Manufacturer's name GRUNDFOS					
Model Number		10S007-200		HP 0.75 Volt 230	
Length of drop pipe		40 ft		Capacity 10 g.p. Typ Submersible	
Abandoned					
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No					
Variance					
Was a variance granted from the MDH for this well? ☐ Yes ☒ No					
Miscellaneous					
First Bedrock		Aquifer			
Last Strat		Depth to Bedrock ft			
Located by					
Locate Method					
System		UTM - NAD83, Zone 15, Meters		X Y	
Unique Number Verification				Input Date	
Angled Drill Hole					
Well Contractor					
Antlers Well Drilling		1448		PINK, CHRIS	
Licensee Business		Lic. or Reg. No.		Name of Driller	