

885908

County Washington
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date

Update Date03/19/2026

Received Date11/17/2025

Well NameTownshipRangeDir SectionSubsection KOHLER, GARY3220W 22ACA					Well DepthDepth CompletedDate Well Completed 260 ft.260 ft.09/04/2025																																		
ElevationElev. Method					Drill MethodNon-specified RotaryDrill FluidBentonite																																		
Address C/W14034 205TH ST N SCANDIA MN 55073					Use domesticStatusActive																																		
Stratigraphy Information <table><thead><tr><th>Geological Material</th><th>From</th><th>To (ft.)</th><th>Color</th><th>Hardness</th></tr></thead><tbody><tr><td>SAND & GRAVEL</td><td>0</td><td>30</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY & ROCKS</td><td>30</td><td>147</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SANDROCK</td><td>147</td><td>189</td><td>YELLOW</td><td>SOFT</td></tr><tr><td>LIME</td><td>189</td><td>255</td><td>TAN</td><td>HARD</td></tr><tr><td>SANDROCK</td><td>255</td><td>260</td><td>BROWN</td><td>MEDIUM</td></tr></tbody></table>					Geological Material	From	To (ft.)	Color	Hardness	SAND & GRAVEL	0	30	BROWN	SOFT	CLAY & ROCKS	30	147	BROWN	SOFT	SANDROCK	147	189	YELLOW	SOFT	LIME	189	255	TAN	HARD	SANDROCK	255	260	BROWN	MEDIUM	Well Hydrofractured?Yes☐No☒FromTo				
					Geological Material	From	To (ft.)	Color	Hardness																														
					SAND & GRAVEL	0	30	BROWN	SOFT																														
					CLAY & ROCKS	30	147	BROWN	SOFT																														
					SANDROCK	147	189	YELLOW	SOFT																														
					LIME	189	255	TAN	HARD																														
					SANDROCK	255	260	BROWN	MEDIUM																														
					Casing TypeSingle casingJointWelded																																		
					Drive Shoe?Yes☒No☐Above/Below																																		
					Casing DiameterWeightHole Diameter 4 in. To190 ft.10.79 lbs./ft.8 in. To190 ft. 4 in. To260 ft.																																		
Open HoleFrom190 ft.To260 ft.																																							
Screen?☐TypeMake																																							
Static Water Level 130 ft.land surfaceMeasure09/04/2025																																							
Pumping Level (below land surface) 180 ft.2 hrs.Pumping at20 g.p.m.																																							
Wellhead Completion Pitless adapter manufacturerWHITEWATERModel864X5.5 ☒ Casing Protection☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																							
Grouting InformationWell Grouted?☒ Yes☐ No☐ Not Specified MaterialAmountFromTo neat cement2 Cubic yardsft.190 ft.																																							
Nearest Known Source of Contamination 60 feetSouth DirectionSeptic tank/drain field Type Well disinfected upon completion?☒ Yes☐ No																																							
Pump☐ Not InstalledDate Installed09/04/2025 Manufacturer's nameGRUNDFOS Model Number10S10-15HP1Volt230 Length of drop pipe168 ftCapacity10 g.p.TypSubmersible																																							
Abandoned Does property have any not in use and not sealed well(s)?☐ Yes☒ No																																							
Variance Was a variance granted from the MDH for this well?☐ Yes☒ No																																							
Miscellaneous First BedrockAquifer Last StratDepth to Bedrockft Located by Locate Method SystemUTM - NAD83, Zone 15, MetersXY Unique Number VerificationInput Date																																							
Angled Drill Hole																																							
Well Contractor Kimmes Bauer Well Drilling,1540LANDRY, A. Licensee BusinessLic. or Reg. No.Name of Driller																																							