

885915

County Le Sueur
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 12/04/2025
Received Date 11/08/2025

Well Name BAKER, ROSS	Township 109	Range 24	Dir W	Section 19	Subsection CBC																									
Elevation Elev. Method																														
Address Well 49697 251ST AV MADISON MN 56063 Contact 45219 267TH AV CLEVELAND MN 56017																														
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND</td><td>0</td><td>45</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND+GRAVEL</td><td>45</td><td>88</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>88</td><td>420</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND+GRAVEL</td><td>420</td><td>438</td><td>BROWN</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	SAND	0	45	BROWN	SOFT	SAND+GRAVEL	45	88	BROWN	SOFT	CLAY	88	420	GRAY	MEDIUM	SAND+GRAVEL	420	438	BROWN	SOFT
Geological Material	From	To (ft.)	Color	Hardness																										
SAND	0	45	BROWN	SOFT																										
SAND+GRAVEL	45	88	BROWN	SOFT																										
CLAY	88	420	GRAY	MEDIUM																										
SAND+GRAVEL	420	438	BROWN	SOFT																										
Well Depth 438 ft. Depth Completed 438 ft. Date Well Completed 10/15/2025																														
Drill Method Non-specified Rotary Drill Fluid Bentonite																														
Use domestic Status Active																														
Well Hydrofractured? Yes ☐ No ☒ From To																														
Casing Type Single casing Joint Welded																														
Drive Shoe? Yes ☒ No ☐ Above/Below																														
Casing Diameter Weight 4 in. To 432 ft. 10.79 lbs./ft.																														
Open Hole From ft. To ft.																														
Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 2 in. 10 5 ft. 232 ft. 238 ft.																														
Static Water Level 200 ft. land surface Measure 10/15/2025																														
Pumping Level (below land surface) 360 ft. 2 hrs. Pumping at 20 g.p.m.																														
Wellhead Completion Pitless adapter manufacturer Model ☒ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																														
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 27 Sacks ft. 432 ft.																														
Nearest Known Source of Contamination 150 feet Southwes Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																														
Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																														
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																														
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																														
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																														
Angled Drill Hole																														
Well Contractor Kimmes Bauer Well Drilling, 1540 LANDRY, A Licensee Business Lic. or Reg. No. Name of Driller																														