

886245

County Douglas
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/30/2025
Update Date 05/30/2025
Received Date 12/05/2024

Well Name GILLUND,	Township 128	Range 37	Dir W	Section 3	Subsection AAA
Elevation	Elev. Method				
Address					
Contact 2242 120 OLD CR NE ALEXANDRIA MN 56308					
Well 4800 39TH AV NE ALEXANDRIA MN 56308					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
SANDY CLAY		0	7	BROWN	MEDIUM
CLAY		7	19	BLUE	MEDIUM
SAND		19	25	GRAY	SOFT
CLAY		25	82	BLUE	MEDIUM
SAND		82	94	GRAY	MEDIUM
CLAY		94	255	BLUE	M.HARD
SAND STREAKS		255	260	GRAY	MEDIUM

Well Depth 260 ft.	Depth Completed 260 ft.	Date Well Completed 10/27/2024			
Drill Method	Non-specified Rotary		Drill Fluid	Qwik gel	
Use	domestic				Status Active
Well Hydrofractured?	Yes	☐	No	☒	From To
Casing Type	Other		Joint		
Drive Shoe?	Yes	☐	No	☒	Above/Below
Casing Diameter		Weight			
4 in. To	255 ft.	lbs./ft.			
4 in. To	200 ft.	lbs./ft.			
Open Hole					
		From	ft.	To	ft.
Screen?	☒	Type		telescoping	
Diameter	Slot/Gauze	Length		Make JOHNSON	
4 in.	10	5 ft.		255 ft.	260 ft.
Static Water Level					
23 ft.	land surface			Measure	10/27/2024
Pumping Level (below land surface)					
260 ft.	2 hrs.	Pumping at		50	g.p.m.
Wellhead Completion					
Pitless adapter manufacturer			Model		
☐	Casing Protection		☒ 12 in. above grade		
☐	At-grade (Environmental Wells and Borings ONLY)				
Grouting Information		Well Grouted?		☒ Yes	☐ No
				☐ Not Specified	
Material		Amount		From	To
cuttings				75	ft. 250 ft.
pearock				250	ft. 260 ft.
bentonite					ft. 75 ft.
Nearest Known Source of Contamination					
50 feet		West Direction		Sewer Type	
Well disinfected upon completion?		☒ Yes		☐ No	
Pump		☐ Not Installed	Date Installed		
Manufacturer's name		FPS			
Model Number		SERIES 6	HP	1	Volt 230
Length of drop pipe		ft	Capacity	18	g.p. Typ Submersible
Abandoned					
Does property have any not in use and not sealed well(s)?				☐ Yes	☒ No
Variance					
Was a variance granted from the MDH for this well?				☐ Yes	☒ No
Miscellaneous					
First Bedrock		Aquifer			
Last Strat		Depth to Bedrock		ft	
Located by					
Locate Method					
System		UTM - NAD83, Zone 15, Meters		X	Y
Unique Number Verification				Input Date	
Angled Drill Hole					
Well Contractor					
Darin Weisel Well Service		1359		WEISEL, OWEN.	
Licensee Business		Lic. or Reg. No.		Name of Driller	

Minnesota Well Index Report	886245	Printed on 08/13/2026 HE-01205-15
-----------------------------	--------	--------------------------------------