

888259

County Kandiyohi
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/23/2026
Update Date 03/23/2026
Received Date 11/10/2025

Well Name KREBSBACH	Township 120	Range 33	Dir W	Section 30	Subsection ABA
Elevation	Elev. Method				
Address					
Contact 7585 12TH ST NW WILLMAR MN 56201					
Well 5935 4 CR NE ATWATER MN					
Stratigraphy Information					
Geological Material		From	To (ft.)	Color	Hardness
TOPSOIL		0	2		
CLAY - SANDY		2	18	YELLOW	
CLAY		18	20	BROWN	
CLAY		20	22	BLUE	
CLAY		22	30	BROWN	
CLAY		30	52	BLUE	
SAND		52	62		
CLAY SAND MIX		62	70	BLUE	

Well Depth 70 ft.	Depth Completed 61 ft.	Date Well Completed 10/09/2025			
Drill Method	Non-specified Rotary		Drill Fluid	Bentonite	
Use	domestic				Status Active
Well Hydrofractured?		Yes ☐	No ☒	From	To
Casing Type		Single casing		Joint	
Drive Shoe?	Yes ☐	No ☒	Above/Below		
Casing Diameter		Weight		Hole Diameter	
5 in. To		56 ft. lbs./ft.		7.8 in. To ft.	
Open Hole					
From		ft.		To ft.	
Screen? ☒	Type plastic		Make JOHNSON		
Diameter	Slot/Gauze	Length		Set	
5 in.	15	5 ft.		56 ft.	61 ft.
Static Water Level					
29 ft.		land surface		Measure	08/04/2025
Pumping Level (below land surface)					
50 ft.		2 hrs. Pumping at		20 g.p.m.	
Wellhead Completion					
Pitless adapter manufacturer		MERRILL		Model	MCK
☐ Casing Protection		☐ 12 in. above grade			
☐ At-grade (Environmental Wells and Borings ONLY)					
Grouting Information		Well Grouted? ☒ Yes ☐ No ☐ Not Specified			
Material		Amount		From	To
bentonite		4 Sacks		ft.	50 ft.
Nearest Known Source of Contamination					
50 feet		Northeas Direction		Sewer Type	
Well disinfected upon completion?		☒ Yes ☐ No			
Pump ☐ Not Installed		Date Installed		10/09/2025	
Manufacturer's name		GRUNDFOS			
Model Number	10SQE05-	HP	0.5	Volt	230
Length of drop pipe	40 ft	Capacity	10 g.p.	Typ	Submersible
Abandoned					
Does property have any not in use and not sealed well(s)?				☐ Yes	☒ No
Variance					
Was a variance granted from the MDH for this well?				☐ Yes	☒ No
Miscellaneous					
First Bedrock		Aquifer			
Last Strat		Depth to Bedrock		ft	
Located by					
Locate Method					
System	UTM - NAD83, Zone 15, Meters			X	Y
Unique Number Verification				Input Date	
Angled Drill Hole					
Well Contractor					
Thein Well Co., Inc.		1337		THEIN, T	
Licensee Business		Lic. or Reg. No.		Name of Driller	

Minnesota Well Index Report	888259	Printed on 08/13/2026 HE-01205-15
-----------------------------	--------	--------------------------------------