

888263

County Kandiyohi
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 03/23/2026
Update Date 03/23/2026
Received Date 12/22/2025

Well Name MAHN, SCOTT					Township 120	Range 33	Dir W	Section 36	Subsection CDC	Well Depth 68 ft.		Depth Completed 60 ft.		Date Well Completed 10/30/2025																																		
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Bentonite																																				
Address C/W 19950 30TH AV NE ATWATER MN 56209										Use domestic		Status Active																																				
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>1</td><td></td><td></td></tr><tr><td>SAND & CLAY</td><td>1</td><td>26</td><td>YELLOW</td><td></td></tr><tr><td>CLAY</td><td>26</td><td>37</td><td>BROWN</td><td></td></tr><tr><td>SAND</td><td>37</td><td>47</td><td></td><td></td></tr><tr><td>GRAVEL & SAND</td><td>47</td><td>62</td><td></td><td></td></tr><tr><td>CLAY</td><td>62</td><td>68</td><td>BLUE</td><td></td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	1			SAND & CLAY	1	26	YELLOW		CLAY	26	37	BROWN		SAND	37	47			GRAVEL & SAND	47	62			CLAY	62	68	BLUE		Well Hydrofractured? Yes ☐ No ☒ From		To	
										Geological Material	From	To (ft.)	Color	Hardness																																		
										TOP SOIL	0	1																																				
										SAND & CLAY	1	26	YELLOW																																			
										CLAY	26	37	BROWN																																			
										SAND	37	47																																				
										GRAVEL & SAND	47	62																																				
										CLAY	62	68	BLUE																																			
										Casing Type Single casing		Joint																																				
										Drive Shoe? Yes ☐ No ☒		Above/Below																																				
Casing Diameter 5 in. To		Weight 55 ft. lbs./ft.		Hole Diameter 7.8 in. To ft.																																												
Open Hole <table><tr><td>From</td><td>ft.</td><td>To</td><td>ft.</td></tr><tr><td>Screen? ☒</td><td>Type plastic</td><td colspan="2">Make JOHNSON</td></tr><tr><td>Diameter</td><td>Slot/Gauze</td><td>Length</td><td>Set</td></tr><tr><td>5 in.</td><td>15</td><td>5 ft.</td><td>55 ft. 60 ft.</td></tr></table>						From	ft.	To	ft.	Screen? ☒	Type plastic	Make JOHNSON		Diameter	Slot/Gauze	Length	Set	5 in.	15	5 ft.	55 ft. 60 ft.																											
From	ft.	To	ft.																																													
Screen? ☒	Type plastic	Make JOHNSON																																														
Diameter	Slot/Gauze	Length	Set																																													
5 in.	15	5 ft.	55 ft. 60 ft.																																													
Static Water Level 27 ft. land surface Measure 09/16/2025																																																
Pumping Level (below land surface) 50 ft. 2 hrs. Pumping at 30 g.p.m.																																																
Wellhead Completion Pitless adapter manufacturer MERRILL Model MCK ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																																
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 5 Sacks ft. 50 ft.																																																
Nearest Known Source of Contamination 50 feet West Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																																																
Pump ☐ Not Installed Date Installed 10/30/2025 Manufacturer's name STA-RITE Model Number S10P4JP05- HP 0.5 Volt 230 Length of drop pipe 40 ft Capacity 10 g.p. Typ Submersible																																																
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																																
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																																
Miscellaneous First Bedrock Last Strat Aquifer Located by Depth to Bedrock ft. Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																																
Angled Drill Hole																																																
Well Contractor Thein Well Co., Inc. 1337 THEIN, A Licensee Business Lic. or Reg. No. Name of Driller																																																