

888290

County Otter Tail
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 05/07/2026
Received Date 02/02/2026

Well Name MEGOWAN,	Township 134	Range 40	Dir Section W 2	Subsection CCB	Well Depth 67 ft.	Depth Completed 64 ft.	Date Well Completed 11/17/2025																														
Elevation	Elev. Method				Drill Method Non-specified Rotary	Drill Fluid Qwik gel																															
Address C/W 33042 14 HY RICHVILLE MN					Use domestic	Status Active																															
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>2</td><td>BLACK</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>2</td><td>12</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>12</td><td>38</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>CLAY / SAND</td><td>38</td><td>56</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND</td><td>56</td><td>67</td><td>GRAY</td><td>MEDIUM</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	2	BLACK	MEDIUM	SAND	2	12	BROWN	MEDIUM	SAND	12	38	GRAY	MEDIUM	CLAY / SAND	38	56	GRAY	MEDIUM	SAND	56	67	GRAY	MEDIUM	Well Hydrofractured? Yes ☐ No ☒ From To		
					Geological Material	From	To (ft.)	Color	Hardness																												
					TOP SOIL	0	2	BLACK	MEDIUM																												
					SAND	2	12	BROWN	MEDIUM																												
					SAND	12	38	GRAY	MEDIUM																												
					CLAY / SAND	38	56	GRAY	MEDIUM																												
					SAND	56	67	GRAY	MEDIUM																												
					Casing Type Single casing Joint																																
					Drive Shoe? Yes ☐ No ☒ Above/Below																																
					Casing Diameter 4 in. To 60 ft. lbs./ft.			Hole Diameter 6 in. To 67 ft.																													
Open Hole From ft. To ft.																																					
Screen? ☒ Type stainless Make JOHNSON																																					
Diameter Slot/Gauze Length Set																																					
4 in. 12 4 ft. 60 ft. 64 ft.																																					
Static Water Level 12 ft. land surface Measure 11/17/2025																																					
Pumping Level (below land surface) 50 ft. 1 hrs. Pumping at 100 g.p.m.																																					
Wellhead Completion Pitless adapter manufacturer Model 4BO ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																					
Material Amount From To																																					
cuttings 50 ft. 60 ft.																																					
other 2 Sacks ft. 50 ft.																																					
Nearest Known Source of Contamination feet Direction Type																																					
Well disinfected upon completion? ☒ Yes ☐ No																																					
Pump ☐ Not Installed Date Installed																																					
Manufacturer's name GRUNDFOS																																					
Model Number SQ07-200 HP 0.75 Volt 230																																					
Length of drop pipe 20 ft Capacity 15 g.p. Typ Submersible																																					
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																					
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																					
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																					
Angled Drill Hole																																					
Well Contractor Licensee Business Lic. or Reg. No. BURMEISTER, B Name of Driller																																					