

889062

County Crow Wing
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 06/03/2025
Received Date 12/17/2024

Well Name WHITE,	Township 43	Range 28	Dir W	Section 2	Subsection ACD	Well Depth 88 ft.	Depth Completed 88 ft.	Date Well Completed 10/28/2024
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid	Additive (+ Bentonite)
Address						Use domestic	Status Active	
Well 5514 BANYAN DR N GARRISON MN						Well Hydrofractured? Yes ☐ No ☒ From To		
Contact 12617 ELM PK ROGERS MN 55374						Casing Type Single casing Joint		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☐ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
SAND & ROCK		0	2	BROWN	MEDIUM	4 in. To 80 ft. lbs./ft. 6.5 in. To 88 ft.		
CLAY		2	13		MEDIUM			
CLAY & ROCK		13	48	GRAY	MEDIUM			
"" & GRAVEL		48	69	BROWN	MEDIUM			
SAND		69	88	BROWN	MEDIUM			
Open Hole						From	ft.	To ft.
Screen? ☒						Type stainless	Make JOHNSON	
Diameter						Slot/Gauze	Length	Set
2 in.						10	8 ft.	80 ft. 88 ft.
Static Water Level								
13 ft.						land surface	Measure	10/28/2024
Pumping Level (below land surface)								
75 ft.						1 hrs.	Pumping at	5 g.p.m.
Wellhead Completion								
Pitless adapter manufacturer						MONITOR	Model	SNAPPY
☐ Casing Protection						☐ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material						Amount	From	To
bentonite						4 Sacks	ft.	50 ft.
Nearest Known Source of Contamination								
50 feet						Direction	Type	
Well disinfected upon completion?						☒ Yes ☐ No		
Pump ☐ Not Installed						Date Installed		
Manufacturer's name						STA-RITE		
Model Number						HP 0.5	Volt 230	
Length of drop pipe 75 ft						Capacity 10 g.p.	Typ	Submersible
Abandoned								
Does property have any not in use and not sealed well(s)?						☐ Yes ☒ No		
Variance								
Was a variance granted from the MDH for this well?						☐ Yes ☒ No		
Miscellaneous								
First Bedrock						Aquifer		
Last Strat						Depth to Bedrock	ft	
Located by								
Locate Method								
System UTM - NAD83, Zone 15, Meters						X	Y	
Unique Number Verification						Input Date		
Angled Drill Hole								
Well Contractor								
Hasskamp Bros. Well Drilling						1585	CHAD & CORY	
Licensee Business						Lic. or Reg. No.	Name of Driller	