

889726

County Anoka
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 01/27/2026
Received Date 10/21/2025

Well Name RYGWALL, JEFF					Township 32	Range 24	Dir W	Section 29	Subsection CAB	Well Depth 120 ft.		Depth Completed 120 ft.		Date Well Completed 09/16/2025																																														
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Bentonite																																																
Address										Use domestic		Status Active																																																
C/W 14339 WOODBINE ST NW ANDOVER MN 55304										Well Hydrofractured?		Yes ☐		No ☒		From To																																												
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>1</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND</td><td>1</td><td>6</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>6</td><td>15</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>SAND+GRAVEL</td><td>15</td><td>22</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY+ROCKS</td><td>22</td><td>77</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>77</td><td>97</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>SAND+GRAVEL</td><td>97</td><td>118</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>118</td><td>120</td><td>BROWN</td><td>MEDIUM</td></tr></table>										Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	1	BROWN	SOFT	SAND	1	6	BROWN	SOFT	CLAY	6	15	BROWN	MEDIUM	SAND+GRAVEL	15	22	BROWN	SOFT	CLAY+ROCKS	22	77	BROWN	MEDIUM	CLAY	77	97	GRAY	MEDIUM	SAND+GRAVEL	97	118	GRAY	SOFT	CLAY	118	120	BROWN	MEDIUM	Casing Type Single casing		Joint			
										Geological Material	From	To (ft.)	Color	Hardness																																														
										TOP SOIL	0	1	BROWN	SOFT																																														
										SAND	1	6	BROWN	SOFT																																														
										CLAY	6	15	BROWN	MEDIUM																																														
										SAND+GRAVEL	15	22	BROWN	SOFT																																														
										CLAY+ROCKS	22	77	BROWN	MEDIUM																																														
										CLAY	77	97	GRAY	MEDIUM																																														
										SAND+GRAVEL	97	118	GRAY	SOFT																																														
										CLAY	118	120	BROWN	MEDIUM																																														
Drive Shoe?		Yes ☐		No ☒		Above/Below																																																						
Casing Diameter		Weight		Hole Diameter																																																								
4 in. To		113 ft. 2.09 lbs./ft.		8 in. To 120 ft.																																																								
Open Hole										From		ft.		To		ft.																																												
Screen?		☒		Type stainless		Make JOHNSON																																																						
Diameter		Slot/Gauze		Length		Set																																																						
4 in.		18		4 ft.		113 ft.		117 ft.																																																				
Static Water Level										21 ft.		land surface		Measure		09/16/2025																																												
Pumping Level (below land surface)										117 ft.		1 hrs.		Pumping at		50 g.p.m.																																												
Wellhead Completion										Pitless adapter manufacturer				BULLDOG		Model 4X1																																												
☐ Casing Protection										☒ 12 in. above grade																																																		
☐ At-grade (Environmental Wells and Borings ONLY)																																																												
Grouting Information										Well Grouted?		☒ Yes		☐ No		☐ Not Specified																																												
Material										Amount		From		To																																														
cement-sand												103		ft. 120		ft.																																												
other										14 Sacks				ft. 103		ft.																																												
Nearest Known Source of Contamination										30 feet		North Direction		Sewer Type																																														
Well disinfected upon completion?										☒ Yes		☐ No																																																
Pump										☐ Not Installed		Date Installed		09/24/2025																																														
Manufacturer's name										FRANKLIN																																																		
Model Number										10FS07		HP 0.75		Volt 230																																														
Length of drop pipe										60 ft		Capacity 10 g.p.		Typ Submersible																																														
Abandoned										Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																																		
Variance										Was a variance granted from the MDH for this well? ☒ Yes ☐ No																																																		
Miscellaneous										First Bedrock																																																		
Last Strat										Aquifer																																																		
Located by										Depth to Bedrock																																																		
Locate Method										ft																																																		
System										UTM - NAD83, Zone 15, Meters		X		Y																																														
Unique Number Verification										Input Date																																																		
Angled Drill Hole																																																												
Well Contractor										Mark J Traut Wells, Inc.																																																		
Licensee Business										1404		TERRES, R																																																
										Lic. or Reg. No.		Name of Driller																																																