

889827

County Chippewa
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date

Update Date02/09/2026

Received Date10/31/2025

Well Name DAHLVANG,	Township 117	Range 40	Dir W	Section 20	Subsection DDA	Well Depth 605 ft.	Depth Completed 605 ft.	Date Well Completed 10/05/2025																																																																	
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite																																																																		
Address						Use domestic	Status Active																																																																		
C/W 6079 50TH AV SW MONTEVIDEO MN 56265						Well Hydrofractured? Yes ☒ No ☐	From 150 ft.	To 605 ft.																																																																	
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOPSOIL</td><td>0</td><td>1</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>1</td><td>4</td><td>YELLOW</td><td>SOFT</td></tr><tr><td>GRANITE</td><td>4</td><td>20</td><td>YEL/WHT</td><td>HARD</td></tr><tr><td>GRANITE</td><td>20</td><td>60</td><td>VARIED</td><td>HARD</td></tr><tr><td>GRANITE</td><td>60</td><td>180</td><td>BLK/RED</td><td>HARD</td></tr><tr><td>GRANITE</td><td>180</td><td>300</td><td>WHT/RED</td><td>HARD</td></tr><tr><td>GRANITE</td><td>300</td><td>340</td><td>PNK/PUR</td><td>V.HARD</td></tr><tr><td>GRANITE</td><td>340</td><td>380</td><td>VARIED</td><td>HARD</td></tr><tr><td>GRANITE</td><td>380</td><td>470</td><td>VARIED</td><td>HARD</td></tr><tr><td>GRANITE</td><td>470</td><td>500</td><td>RED/WHT</td><td>HARD</td></tr><tr><td>GRANITE</td><td>500</td><td>520</td><td>BLK/GRN</td><td>HARD</td></tr><tr><td>GRANITE</td><td>520</td><td>605</td><td>RED/BLK</td><td>HARD</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOPSOIL	0	1	BLACK	SOFT	CLAY	1	4	YELLOW	SOFT	GRANITE	4	20	YEL/WHT	HARD	GRANITE	20	60	VARIED	HARD	GRANITE	60	180	BLK/RED	HARD	GRANITE	180	300	WHT/RED	HARD	GRANITE	300	340	PNK/PUR	V.HARD	GRANITE	340	380	VARIED	HARD	GRANITE	380	470	VARIED	HARD	GRANITE	470	500	RED/WHT	HARD	GRANITE	500	520	BLK/GRN	HARD	GRANITE	520	605	RED/BLK	HARD	Casing Type Single casing	Joint Threaded	
						Geological Material	From	To (ft.)	Color	Hardness																																																															
						TOPSOIL	0	1	BLACK	SOFT																																																															
						CLAY	1	4	YELLOW	SOFT																																																															
						GRANITE	4	20	YEL/WHT	HARD																																																															
						GRANITE	20	60	VARIED	HARD																																																															
						GRANITE	60	180	BLK/RED	HARD																																																															
						GRANITE	180	300	WHT/RED	HARD																																																															
						GRANITE	300	340	PNK/PUR	V.HARD																																																															
						GRANITE	340	380	VARIED	HARD																																																															
GRANITE	380	470	VARIED	HARD																																																																					
GRANITE	470	500	RED/WHT	HARD																																																																					
GRANITE	500	520	BLK/GRN	HARD																																																																					
GRANITE	520	605	RED/BLK	HARD																																																																					
Drive Shoe? Yes ☒ No ☐						Above/Below																																																																			
Casing Diameter 6 in.						Weight 20 ft. lbs./ft.		Hole Diameter 9.8 in. To 20 ft. 6 in. To 605 ft.																																																																	
Open Hole From 20 ft. To 605 ft.						Screen? ☐		Type Make																																																																	
Static Water Level 40 ft. land surface						Measure 10/05/2025																																																																			
Pumping Level (below land surface) 300 ft. 20 hrs. Pumping at						10 g.p.m.																																																																			
Wellhead Completion Pitless adapter manufacturer ☐ Casing Protection ☐ At-grade (Environmental Wells and Borings ONLY)						MAAS Model 6J1 ☐ 12 in. above grade																																																																			
Grouting Information Material neat cement						Well Grouted? ☒ Yes ☐ No ☐ Not Specified Amount 15 Sacks From ft. 20 ft.																																																																			
Nearest Known Source of Contamination 150 feet Northwes Direction Well disinfected upon completion? ☒ Yes ☐ No						Sewer Type																																																																			
Pump ☐ Not Installed Manufacturer's name GOULDS Model Number G SERIES Length of drop pipe 500 ft						Date Installed 10/06/2025 HP 1.5 Capacity 5 g.p. Volt 230 Typ Submersible																																																																			
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																																																									
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																																																									
Miscellaneous First Bedrock Last Strat Located by Locate Method System UTM - NAD83, Zone 15, Meters Unique Number Verification						Aquifer Depth to Bedrock ft X Y Input Date																																																																			
Angled Drill Hole																																																																									
Well Contractor Ervin Drilling & Pump, LLC Licensee Business						4007 Lic. or Reg. No. ERVIN, K Name of Driller																																																																			