

889842

County Redwood
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 05/07/2026
Received Date 02/20/2026

Well Name ZITZMANN,					Township 112	Range 36	Dir W	Section 1	Subsection CCB	Well Depth 605 ft.			Depth Completed 605 ft.			Date Well Completed 08/15/2025		
Elevation					Elev. Method					Drill Method Non-specified Rotary			Drill Fluid Bentonite					
Address										Use domestic			Status Active					
Contact					309 WESTWOOD DR REDWOOD FALLS MN 56283					Well Hydrofractured?			Yes ☒	No ☐	From 300 ft.	To 605 ft.		
Well					460 WESTWOOD DR REDWOOD FALLS MN 56283					Casing Type Single casing			Joint Threaded					
Stratigraphy Information										Drive Shoe?			Yes ☒	No ☐	Above/Below			
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter			Weight			Hole Diameter						
GRAVEL - ROCKS		0	18	YELLOW	HARD	6	in.	To	105	ft.	lbs./ft.	9.9	in.	To	105	ft.		
CLAY - ROCKS		18	43	YELLOW	HARD	6	in.	To	605	ft.		6	in.	To	605	ft.		
CLAY		43	62	GRAY	MED-HRD													
DECOMP		62	67	RED/BRN	SFT-MED													
DECOMP		67	96	GREEN	MED-HRD													
GRANITE		96	210	BLACK	HARD													
GRANITE		210	340	RED/WHT	HARD													
GRANITE		340	390	BLK/RED	V.HARD													
GRANITE		390	460	RED/WHT	HARD													
GRANITE		460	540	BLK/RED	HARD													
GRANITE: COLOR-		540	570	VARIED	HARD													
GRANITE		570	605	RED/GRN	HARD													
Open Hole																		
From 105 ft. To 605 ft.																		
Screen? ☐ Type Make																		
Static Water Level																		
3 ft. land surface Measure 08/15/2025																		
Pumping Level (below land surface)																		
350 ft. 72 hrs. Pumping at 10 g.p.m.																		
Wellhead Completion																		
Pitless adapter manufacturer BAKER Model 6X1.25																		
☐ Casing Protection ☐ 12 in. above grade																		
☐ At-grade (Environmental Wells and Borings ONLY)																		
Grouting Information																		
Well Grouted? ☒ Yes ☐ No ☐ Not Specified																		
Material Amount From To																		
bentonite 10 Sacks ft. 105 ft.																		
Nearest Known Source of Contamination																		
65 feet East Direction Sewer Type																		
Well disinfected upon completion? ☒ Yes ☐ No																		
Pump ☐ Not Installed Date Installed 11/11/2025																		
Manufacturer's name GOULDS																		
Model Number 5GS15 HP 1.5 Volt 230																		
Length of drop pipe 480 ft Capacity 5 g.p. Typ Submersible																		
Abandoned																		
Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																		
Variance																		
Was a variance granted from the MDH for this well? ☐ Yes ☒ No																		
Miscellaneous																		
First Bedrock Aquifer																		
Last Strat Depth to Bedrock ft																		
Located by																		
Locate Method																		
System UTM - NAD83, Zone 15, Meters X Y																		
Unique Number Verification Input Date																		
Angled Drill Hole																		
Well Contractor																		
Ervin Drilling & Pump, LLC 4007 ERVIN, K.																		
Licensee Business Lic. or Reg. No. Name of Driller																		
Remarks																		