

890347

County Swift
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/05/2026
Update Date 05/05/2026
Received Date 01/21/2026

Well Name LARSON, LOUIE					Township 120	Range 39	Dir Section W 29	Subsection CAD	Well Depth 65 ft.		Depth Completed 65 ft.		Date Well Completed 10/29/2025																																		
Elevation					Elev. Method					Drill Method Non-specified Rotary		Drill Fluid Bentonite																																			
Address									Use domestic		Status Active																																				
C/W 1065 29 HY SE BENSON MN 56215									Well Hydrofractured? Yes ☐ No ☒		From To																																				
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOPSOIL</td><td>0</td><td>1</td><td>BLACK</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>1</td><td>12</td><td>TAN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>12</td><td>50</td><td>BLUE</td><td>MEDIUM</td></tr><tr><td>CLAY/ ROCKS</td><td>50</td><td>55</td><td>BLU/WHT</td><td>MED-HRD</td></tr><tr><td>SAND</td><td>55</td><td>65</td><td>BLUE</td><td></td></tr><tr><td>CLAY</td><td>65</td><td>65</td><td></td><td></td></tr></table>									Geological Material	From	To (ft.)	Color	Hardness	TOPSOIL	0	1	BLACK	MEDIUM	CLAY	1	12	TAN	MEDIUM	CLAY	12	50	BLUE	MEDIUM	CLAY/ ROCKS	50	55	BLU/WHT	MED-HRD	SAND	55	65	BLUE		CLAY	65	65			Casing Type Single casing		Joint	
									Geological Material	From	To (ft.)	Color	Hardness																																		
									TOPSOIL	0	1	BLACK	MEDIUM																																		
									CLAY	1	12	TAN	MEDIUM																																		
									CLAY	12	50	BLUE	MEDIUM																																		
									CLAY/ ROCKS	50	55	BLU/WHT	MED-HRD																																		
									SAND	55	65	BLUE																																			
									CLAY	65	65																																				
									Drive Shoe? Yes ☐ No ☒		Above/Below																																				
									Casing Diameter 4 in. To 60 ft.		Weight lbs./ft.		Hole Diameter 6.7 in. To 65 ft.																																		
Open Hole From ft. To ft.		Screen? ☒		Type telescoping		Make JOHNSON																																									
Diameter Slot/Gauze		Length Set																																													
4 in. 18		5 ft. 60		ft. 65		ft.																																									
Static Water Level 2 ft. land surface Measure 10/29/2025																																															
Pumping Level (below land surface) 20 ft. 1 hrs. Pumping at 50 g.p.m.																																															
Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																															
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To high solids bentonite 6 Sacks ft. 60 ft.																																															
Nearest Known Source of Contamination 120 feet Northwes Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																																															
Pump ☒ Not Installed Date Installed Manufacturer's name Model Number HP Volt Length of drop pipe ft Capacity g.p. Typ																																															
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																															
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																															
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																															
Angled Drill Hole																																															
Well Contractor Steffl Drilling and Pump, Inc. 1551 GJERDE, M Licensee Business Lic. or Reg. No. Name of Driller																																															