

890509

County Stearns
Quad Belgrade
Quad ID 143A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 06/17/2025
Update Date 01/06/2026
Received Date 04/14/2025

Well Name LISEN, BILL					Township 123	Range 34	Dir W	Section 30	Subsection CCDABA	Well Depth 43 ft.				Depth Completed 43 ft.				Date Well Completed 04/09/2025			
Elevation 0 ft.					Elev. Method					Drill Method Non-specified Rotary				Drill Fluid Bentonite							
Address										Use irrigation				Status Active							
Well 197 CR BELGRADE MN										Well Hydrofractured? Yes ☐ No ☐				From To							
Contact 36795 240TH ST BELGRADE MN 56312										Casing Type Single casing				Joint							
Stratigraphy Information										Drive Shoe? Yes ☐ No ☐				Above/Below							
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter				Weight				Hole Diameter							
TOPSOIL		0	1	BLACK	SOFT	12 in. To 23 ft. 50 lbs./ft.				17. in. To 43 ft.											
SAND		1	20	BROWN	MEDIUM																
SAND		20	33	GRAY	MEDIUM																
CLAY		33	43	GRAY	HARD																
Open Hole										From	ft.	To	ft.								
Screen?		☒	Type		stainless	Make		JOHNSON													
Diameter		Slot/Gauze		Length		Set															
12 in.		110		10 ft.		23 ft.		33 ft.													
Static Water Level																					
13 ft.		land surface				Measure		04/09/2025													
Pumping Level (below land surface)																					
23 ft.		4 hrs.		Pumping at		400		g.p.m.													
Wellhead Completion																					
Pitless adapter manufacturer					TOPHEAD					Model											
☐ Casing Protection					☐ 12 in. above grade																
☐ At-grade (Environmental Wells and Borings ONLY)																					
Grouting Information										Well Grouted?		☒ Yes	☐ No	☐ Not Specified							
Material					Amount					From		To									
other										ft. 13		ft.									
Nearest Known Source of Contamination																					
feet					Direction					Type											
Well disinfected upon completion?										☒ Yes	☐ No										
Pump										☐ Not Installed	Date Installed										
Manufacturer's name																					
Model Number					HP					Volt											
Length of drop pipe					ft	Capacity		g.p.	Typ												
Abandoned																					
Does property have any not in use and not sealed well(s)?										☐ Yes	☒ No										
Variance																					
Was a variance granted from the MDH for this well?										☐ Yes	☒ No										
Miscellaneous																					
First Bedrock					Aquifer																
Last Strat					Depth to Bedrock					ft											
Located by										Minnesota Department of Health											
Locate Method										GPS SA Off (averaged) (15 meters)											
System					UTM - NAD83, Zone 15, Meters					☒ 343205	☐ 5032482										
Unique Number Verification					Info/GPS from data					Input Date		01/06/2026									
Angled Drill Hole																					
Well Contractor																					
Klimek Bros. Well Drilling,					1864					KLIMEK, DON.											
Licensee Business					Lic. or Reg. No.					Name of Driller											
Remarks																					
Minnesota Well Index Report										890509					Printed on 10/02/2026 HE-01205-15						