

890656

County Itasca
Quad Lawrence
Quad ID 296A

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 03/18/2026
Received Date 11/21/2025

Well Name ECKL,					Township 58	Range 24	Dir W	Section 36	Subsection CDAACB	Well Depth 176 ft.					Depth Completed 176 ft.					Date Well Completed 10/10/2025									
Elevation 1339					Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary															Drill Fluid Bentonite				
Address Well 22565 336 CR BOVEY MN 55709 Contact 6353 STARK RD HARRIS MN 55032										Use domestic															Status Active				
Stratigraphy Information Geological Material From To (ft.) Color Hardness TOP SOIL 0 1 BLACK SOFT CLAY SAND 1 60 BROWN SOFT SAND 60 86 BLUE SOFT CLAY SAND 86 166 BLUE SOFT SAND 166 176 BLUE SOFT										Well Hydrofractured? Yes ☐ No ☒ From To																			
										Casing Type Single casing Joint																			
										Drive Shoe? Yes ☐ No ☒ Above/Below																			
										Casing Diameter 4 in. To 172 ft. 2.25 lbs./ft.															Hole Diameter 7.8 in. To 176 ft.				
										Open Hole From ft. To ft.																			
										Screen? ☒ Type stainless Make JOHNSON																			
										Diameter Slot/Gauze Length Set 4 in. 10 4 ft. 172 ft. 176 ft.																			
										Static Water Level 39 ft. land surface Measure 10/10/2025																			
										Pumping Level (below land surface) 166 ft. 2 hrs. Pumping at 60 g.p.m.																			
										Wellhead Completion Pitless adapter manufacturer AQUA SEAL Model T-SERIES ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																			
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 8 Sacks ft. 70 ft.																													
Nearest Known Source of Contamination 65 feet West Direction Sewer Type Well disinfected upon completion? ☒ Yes ☐ No																													
Pump ☐ Not Installed Date Installed 10/15/2025 Manufacturer's name STA-RITE Model Number S10P4HS05 HP 0.5 Volt 230 Length of drop pipe 61 ft Capacity 10 g.p. Typ Submersible																													
Abandoned Does property have any not in use and not sealed well(s)? ☒ Yes ☐ No																													
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																													
Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 474776 Y 5256394 Unique Number Verification Address verification Input Date 03/18/2026																													
Angled Drill Hole																													
Well Contractor Benes Well Drilling, Inc. 1542 BENES, R Licensee Business Lic. or Reg. No. Name of Driller																													
Remarks																													