

890779

County Waseca
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 05/06/2026
Update Date 05/06/2026
Received Date 11/25/2025

Well Name KEYES, ROY	Township 108	Range 24	Dir Section W 22	Subsection BDA	Well Depth 130 ft.	Depth Completed 130 ft.	Date Well Completed 09/30/2025																														
Elevation	Elev. Method				Drill Method Cable Tool	Drill Fluid Water																															
Address C/W 40603 EAST ELYSIAN LAKE RD JANESVILLE MN					Use domestic	Status Active																															
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOPSOIL</td><td>0</td><td>2</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY</td><td>2</td><td>65</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>65</td><td>68</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND & CLAY</td><td>68</td><td>123</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND</td><td>123</td><td>130</td><td>GRAY</td><td>SOFT</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	TOPSOIL	0	2	BLACK	SOFT	CLAY	2	65	GRAY	SOFT	SAND	65	68	GRAY	SOFT	SAND & CLAY	68	123	GRAY	SOFT	SAND	123	130	GRAY	SOFT	Well Hydrofractured? Yes ☐ No ☒ From To		
					Geological Material	From	To (ft.)	Color	Hardness																												
					TOPSOIL	0	2	BLACK	SOFT																												
					CLAY	2	65	GRAY	SOFT																												
					SAND	65	68	GRAY	SOFT																												
					SAND & CLAY	68	123	GRAY	SOFT																												
					SAND	123	130	GRAY	SOFT																												
					Casing Type Single casing ☐ Joint ☐																																
					Drive Shoe? Yes ☐ No ☐ Above/Below																																
					Casing Diameter Weight Hole Diameter 5 in. To 125 ft. 15 lbs./ft. 5 in. To 130 ft.																																
Open Hole From ft. To ft.																																					
Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 4 in. 12 5 ft. 125 ft. 130 ft.																																					
Static Water Level 58 ft. land surface Measure 09/30/2025																																					
Pumping Level (below land surface) 60 ft. 1 hrs. Pumping at 20 g.p.m.																																					
Wellhead Completion Pitless adapter manufacturer MONITOR Model THREADED ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																					
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To driven casing seal 5 Sacks ft. 70 ft.																																					
Nearest Known Source of Contamination <u>50</u> feet <u>South</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No																																					
Pump ☐ Not Installed Date Installed Manufacturer's name GRUNFOS Model Number <u>10SQ07</u> HP <u>0.75</u> Volt <u>232</u> Length of drop pipe <u>70</u> ft Capacity <u>15</u> g.p. Typ <u>Submersible</u>																																					
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																					
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																					
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																					
Angled Drill Hole																																					
Well Contractor Denn Well Service, Inc. 1699 DENN, G & R Licensee Business Lic. or Reg. No. Name of Driller																																					