

890897

County Chisago
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 02/03/2026
Received Date 12/22/2025

Well Name BOULDER	Township 33	Range 20	Dir W	Section 10	Subsection BBB	Well Depth 204 ft.	Depth Completed 204 ft.	Date Well Completed 10/27/2025
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite	
Address						Use domestic	Status Active	
Well 28834 GLADER BL LINDSTROM MN						Well Hydrofractured? Yes ☐ No ☒ From To		
Contact P O BOX 597 LINDSTROM MN 55045						Casing Type Single casing Joint Glued		
Stratigraphy Information						Drive Shoe? Yes ☐ No ☒ Above/Below		
Geological Material		From	To (ft.)	Color	Hardness	Casing Diameter Weight Hole Diameter		
CLAY		0	52	BROWN	SOFT	4 in. To 204 ft. lbs./ft. 8 in. To 50 ft.		
GRAVEL		52	72	BROWN	SOFT	6.7 in. To 204 ft.		
CLAY, GRAVEL		72	132	BROWN	MEDIUM			
CLAY		132	180	BROWN	SOFT			
SAND		180	192	GRAY	SOFT			
GRAVEL		192	204	GRAY	SOFT			
Open Hole						From	ft.	To ft.
Screen? ☒						Type other	Make BIGFOOT	
Diameter						Slot/Gauze	Length	Set
4 in.						10	20 ft.	182 ft. 202 ft.
Static Water Level								
53 ft.						land surface	Measure	11/04/2025
Pumping Level (below land surface)								
160 ft.						1 hrs.	Pumping at	35 g.p.m.
Wellhead Completion								
Pitless adapter manufacturer						AQUASEAL	Model	4X1
☐ Casing Protection						☒ 12 in. above grade		
☐ At-grade (Environmental Wells and Borings ONLY)								
Grouting Information						Well Grouted? ☒ Yes ☐ No ☐ Not Specified		
Material						Amount	From	To
bentonite						5 Sacks	ft.	50 ft.
Nearest Known Source of Contamination								
20 feet						West Direction	Other Type	
Well disinfected upon completion?						☒ Yes ☐ No		
Pump ☐ Not Installed						Date Installed	11/04/2025	
Manufacturer's name						GOULDS		
Model Number						10CS10	HP	1
Length of drop pipe						120 ft	Capacity	g.p. Typ Submersible
Abandoned								
Does property have any not in use and not sealed well(s)?						☐ Yes ☐ No		
Variance								
Was a variance granted from the MDH for this well?						☐ Yes ☒ No		
Miscellaneous								
First Bedrock						Aquifer		
Last Strat						Depth to Bedrock	ft	
Located by								
Locate Method								
System						UTM - NAD83, Zone 15, Meters	X	Y
Unique Number Verification						Input Date		
Angled Drill Hole								
Well Contractor								
Mork Well Co., Inc.						1877	DANIELSON, C	
Licensee Business						Lic. or Reg. No.	Name of Driller	