

890919

County Anoka
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 01/27/2026
Received Date 12/02/2025

Well Name WEBER, RICK	Township 32	Range 23	Dir W	Section 30	Subsection BAA																																								
Elevation Elev. Method																																													
Address Contact 13118 JACKSON ST NE BLAINE MN 55434 Well 14908 WASHINGTON ST NE HAM LAKE MN																																													
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND</td><td>0</td><td>20</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>20</td><td>46</td><td>BROWN</td><td>SOFT</td></tr><tr><td>SAND, CLAY</td><td>46</td><td>72</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY, ROCKS</td><td>72</td><td>112</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>112</td><td>136</td><td>BROWN</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>136</td><td>192</td><td>GRAY</td><td>MEDIUM</td></tr><tr><td>GRAVEL</td><td>192</td><td>210</td><td>GRAY</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	SAND	0	20	BROWN	SOFT	CLAY	20	46	BROWN	SOFT	SAND, CLAY	46	72	BROWN	SOFT	CLAY, ROCKS	72	112	BROWN	SOFT	CLAY	112	136	BROWN	MEDIUM	CLAY	136	192	GRAY	MEDIUM	GRAVEL	192	210	GRAY	SOFT
Geological Material	From	To (ft.)	Color	Hardness																																									
SAND	0	20	BROWN	SOFT																																									
CLAY	20	46	BROWN	SOFT																																									
SAND, CLAY	46	72	BROWN	SOFT																																									
CLAY, ROCKS	72	112	BROWN	SOFT																																									
CLAY	112	136	BROWN	MEDIUM																																									
CLAY	136	192	GRAY	MEDIUM																																									
GRAVEL	192	210	GRAY	SOFT																																									
Well Depth 210 ft.																																													
Depth Completed 210 ft.																																													
Date Well Completed 10/10/2025																																													
Drill Method Non-specified Rotary																																													
Drill Fluid Bentonite																																													
Use domestic																																													
Status Active																																													
Well Hydrofractured? Yes ☐ No ☒ From To																																													
Casing Type Single casing																																													
Joint Glued																																													
Drive Shoe? Yes ☐ No ☒ Above/Below																																													
Casing Diameter Weight Hole Diameter																																													
4 in. To 210 ft. lbs./ft. 8 in. To 50 ft.																																													
Open Hole From ft. To ft.																																													
Screen? ☒ Type other Make BIG FOOT																																													
Diameter Slot/Gauze Length Set																																													
4 in. 15 10 ft. 198 ft. 208 ft.																																													
Static Water Level																																													
10 ft. land surface Measure 10/10/2025																																													
Pumping Level (below land surface)																																													
ft. hrs. Pumping at g.p.m.																																													
Wellhead Completion																																													
Pitless adapter manufacturer AQUASEAL Model 4X1																																													
☐ Casing Protection ☒ 12 in. above grade																																													
☐ At-grade (Environmental Wells and Borings ONLY)																																													
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																													
Material Amount From To																																													
bentonite 5 Sacks ft. 50 ft.																																													
Nearest Known Source of Contamination																																													
20 feet North Direction Other Type																																													
Well disinfected upon completion? ☒ Yes ☐ No																																													
Pump ☐ Not Installed Date Installed 10/21/2025																																													
Manufacturer's name GOULDS																																													
Model Number 18CS10 HP 1 Volt 230																																													
Length of drop pipe 40 ft Capacity g.p. Typ Submersible																																													
Abandoned																																													
Does property have any not in use and not sealed well(s)? ☐ Yes ☐ No																																													
Variance																																													
Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																													
Miscellaneous																																													
First Bedrock Aquifer																																													
Last Strat Depth to Bedrock ft																																													
Located by																																													
Locate Method																																													
System UTM - NAD83, Zone 15, Meters X Y																																													
Unique Number Verification Input Date																																													
Angled Drill Hole																																													
Well Contractor																																													
Mork Well Co., Inc. 1877 DANIELSON, C																																													
Licensee Business Lic. or Reg. No. Name of Driller																																													