

891158

County Brown
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 04/28/2026
Received Date 01/29/2026

Well Name SWENSON,	Township 110	Range 33	Dir W	Section 27	Subsection DDC	Well Depth 115 ft.	Depth Completed 115 ft.	Date Well Completed 12/16/2025																																			
Elevation	Elev. Method					Drill Method Non-specified Rotary	Drill Fluid Bentonite																																				
Address C/W 30144 27 CR SLEEPY EYE MN 56085						Use domestic	Status Active																																				
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>2</td><td>BLACK</td><td>SOFT</td></tr><tr><td>CLAY SANDY</td><td>2</td><td>18</td><td>YELLOW</td><td>SOFT</td></tr><tr><td>CLAY STONEY</td><td>18</td><td>70</td><td>BLUE</td><td>MEDIUM</td></tr><tr><td>CLAY</td><td>70</td><td>88</td><td>GRAY</td><td>MED-HRD</td></tr><tr><td>SAND & CLAY STRIPS</td><td>88</td><td>112</td><td>GRAY</td><td>SFT-MED</td></tr><tr><td>CLAY</td><td>112</td><td>115</td><td>LT. GRY</td><td>HARD</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	2	BLACK	SOFT	CLAY SANDY	2	18	YELLOW	SOFT	CLAY STONEY	18	70	BLUE	MEDIUM	CLAY	70	88	GRAY	MED-HRD	SAND & CLAY STRIPS	88	112	GRAY	SFT-MED	CLAY	112	115	LT. GRY	HARD	Well Hydrofractured? Yes ☐ No ☒ From To		
						Geological Material	From	To (ft.)	Color	Hardness																																	
						TOP SOIL	0	2	BLACK	SOFT																																	
						CLAY SANDY	2	18	YELLOW	SOFT																																	
						CLAY STONEY	18	70	BLUE	MEDIUM																																	
						CLAY	70	88	GRAY	MED-HRD																																	
						SAND & CLAY STRIPS	88	112	GRAY	SFT-MED																																	
						CLAY	112	115	LT. GRY	HARD																																	
						Casing Type Single casing Joint																																					
						Drive Shoe? Yes ☐ No ☒ Above/Below																																					
Casing Diameter 5 in. To 95 ft. lbs./ft.			Hole Diameter 8.5 in. To 115 ft.																																								
Open Hole From ft. To ft.																																											
Screen? ☒ Type stainless Make JOHNSON Diameter Slot/Gauze Length Set 5 in. 10 20 ft. 95 ft. 115 ft.																																											
Static Water Level 12 ft. land surface Measure 12/16/2025																																											
Pumping Level (below land surface) 65 ft. 3 hrs. Pumping at 40 g.p.m.																																											
Wellhead Completion Pitless adapter manufacturer BAKER Model 5125CBEZLF ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																											
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To other 9 Sacks ft. 85 ft.																																											
Nearest Known Source of Contamination <u>100</u> feet <u>North</u> Direction <u>Septic tank/drain field</u> Type Well disinfected upon completion? ☒ Yes ☐ No																																											
Pump ☐ Not Installed Date Installed <u>12/17/2025</u> Manufacturer's name F&W Model Number <u>4F10S05</u> HP <u>0.5</u> Volt <u>230</u> Length of drop pipe <u>80</u> ft Capacity <u>10</u> g.p. Typ <u>Submersible</u>																																											
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																											
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																											
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																											
Angled Drill Hole																																											
Well Contractor Schaefer Well Co., Inc. 1812 MESSNER, L. Licensee Business Lic. or Reg. No. Name of Driller																																											