

891212

County Martin
Quad Truman SE
Quad ID 36D

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date
Update Date 12/05/2025
Received Date 09/30/2025

Well Name RUSINKO,	Township 104	Range 29	Dir Section W 10	Subsection ADAADC	Well Depth 92 ft.	Depth Completed 92 ft.	Date Well Completed 09/18/2025																				
Elevation 1079	Elev. Method LiDAR 1m DEM (MNDNR)					Drill Method Non-specified Rotary	Drill Fluid Water																				
Address Well 2369 290TH AV WINNEBAGO MN 56098 Contact 2501 PROVIDENCE RD S WAXHAW NC 28173					Use domestic	Status Active																					
Stratigraphy Information					Well Hydrofractured? Yes ☐ No ☐ From To																						
<table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>CLAY</td><td>0</td><td>18</td><td>YELLOW</td><td>SOFT</td></tr><tr><td>SANDY CLAY</td><td>18</td><td>70</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND+GRAVEL</td><td>70</td><td>92</td><td>GRAY</td><td>SOFT</td></tr></table>					Geological Material	From	To (ft.)	Color	Hardness	CLAY	0	18	YELLOW	SOFT	SANDY CLAY	18	70	GRAY	SOFT	SAND+GRAVEL	70	92	GRAY	SOFT	Casing Type Single casing Joint		
Geological Material	From	To (ft.)	Color	Hardness																							
CLAY	0	18	YELLOW	SOFT																							
SANDY CLAY	18	70	GRAY	SOFT																							
SAND+GRAVEL	70	92	GRAY	SOFT																							
					Drive Shoe? Yes ☐ No ☐ Above/Below																						
					<table><tr><td>Casing Diameter</td><td>Weight</td><td>Hole Diameter</td></tr><tr><td>5 in. To 87 ft.</td><td>lbs./ft.</td><td>9 in. To 92 ft.</td></tr></table>			Casing Diameter	Weight	Hole Diameter	5 in. To 87 ft.	lbs./ft.	9 in. To 92 ft.														
Casing Diameter	Weight	Hole Diameter																									
5 in. To 87 ft.	lbs./ft.	9 in. To 92 ft.																									
					Open Hole From ft. To ft.																						
					<table><tr><td>Screen? ☒</td><td>Type stainless</td><td>Make JOHNSON</td></tr><tr><td>Diameter</td><td>Slot/Gauze Length</td><td>Set</td></tr><tr><td>4 in. 12</td><td>5 ft.</td><td>87 ft. 92 ft.</td></tr></table>			Screen? ☒	Type stainless	Make JOHNSON	Diameter	Slot/Gauze Length	Set	4 in. 12	5 ft.	87 ft. 92 ft.											
Screen? ☒	Type stainless	Make JOHNSON																									
Diameter	Slot/Gauze Length	Set																									
4 in. 12	5 ft.	87 ft. 92 ft.																									
					Static Water Level 26.8 ft. land surface Measure 09/18/2025																						
					Pumping Level (below land surface) 60 ft. 1 hrs. Pumping at 20 g.p.m.																						
					Wellhead Completion Pitless adapter manufacturer Model ☐ Casing Protection ☐ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																						
					Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified Material Amount From To bentonite 7 Sacks ft. 85 ft.																						
					Nearest Known Source of Contamination 75 feet South Direction Sewer Type Well disinfected upon completion? ☒ Yes ☐ No																						
					Pump ☐ Not Installed Date Installed Manufacturer's name STA-RITE Model Number HP 0.5 Volt 115 Length of drop pipe 40 ft Capacity g.p. Typ Submersible																						
					Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																						
					Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																						
					Miscellaneous First Bedrock Aquifer Quat. buried Last Strat sand +larger-gray Depth to Bedrock ft Located by Minnesota Geological Survey Locate Method Digitization (Screen) - Map (1:24,000) (15 meters or System UTM - NAD83, Zone 15, Meters X 396459 Y 4853633 Unique Number Verification Address verification Input Date 12/05/2025																						
					Angled Drill Hole																						
					Well Contractor Jadd Seppmann and Sons, 1790 SEPPMANN, T Licensee Business Lic. or Reg. No. Name of Driller																						