

891878

County Otter Tail
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 01/16/2026
Update Date 01/16/2026
Received Date 06/10/2025

Well Name NOWAK, BRIAN	Township 134	Range 39	Dir W	Section 4	Subsection AB																				
Elevation Elev. Method																									
Address Contact 619 7TH ST E WEST FARGO ND 58078 Well 42535 LONG LAKE RD OTTERTAIL MN 56571																									
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>SAND + GRAVEL</td><td>0</td><td>12</td><td></td><td></td></tr><tr><td>CLAY</td><td>12</td><td>25</td><td>GRAY</td><td></td></tr><tr><td>SAND</td><td>25</td><td>38</td><td></td><td></td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	SAND + GRAVEL	0	12			CLAY	12	25	GRAY		SAND	25	38		
Geological Material	From	To (ft.)	Color	Hardness																					
SAND + GRAVEL	0	12																							
CLAY	12	25	GRAY																						
SAND	25	38																							
Well Depth 38 ft. Depth Completed 38 ft. Date Well Completed 06/02/2025																									
Drill Method Non-specified Rotary Drill Fluid Qwik gel																									
Use domestic Status Active																									
Well Hydrofractured? Yes ☐ No ☒ From To																									
Casing Type Single casing Joint																									
Drive Shoe? Yes ☐ No ☒ Above/Below																									
Casing Diameter 4 in. Weight 28 ft. lbs./ft. Hole Diameter 6.7 in. 38 ft.																									
Open Hole From ft. To ft.																									
Screen? ☒ Type plastic Make																									
Diameter 4 in. Slot/Gauze 15 Length 10 ft. Set 28 ft. 38 ft.																									
Static Water Level 12 ft. land surface Measure 05/23/2025																									
Pumping Level (below land surface) 25 ft. 1 hrs. Pumping at 9 g.p.m.																									
Wellhead Completion Pitless adapter manufacturer BULLDOG Model 4X1 ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																									
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																									
Material other Amount 3 Sacks From To ft. 28 ft.																									
Nearest Known Source of Contamination 70 feet North Direction Septic tank/drain field Type Well disinfected upon completion? ☒ Yes ☐ No																									
Pump ☐ Not Installed Date Installed 05/23/2025																									
Manufacturer's name GRUNDFOS HP 0.5 Volt 230																									
Length of drop pipe 20 ft Capacity 10 g.p. Typ Submersible																									
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																									
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																									
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																									
Angled Drill Hole																									
Well Contractor Geo Tech of Minnesota, Inc. 1733 NASH, S Licensee Business Lic. or Reg. No. Name of Driller																									