

891923

County Otter Tail
Quad
Quad ID

MINNESOTA DEPARTMENT OF HEALTH
WELL AND BORING REPORT
Minnesota Statutes Chapter 1031

Entry Date 02/23/2026
Update Date 02/23/2026
Received Date 12/08/2025

Well Name KRUSE, JANICE	Township 134	Range 41	Dir W	Section 36	Subsection CD																																			
Elevation Elev. Method																																								
Address Contact 7591 BANNING WA INVER GROVE HEIGHTS MN 55077 Well 28159 REDHEAD DR UNDERWOOD MN 56586																																								
Stratigraphy Information <table><tr><td>Geological Material</td><td>From</td><td>To (ft.)</td><td>Color</td><td>Hardness</td></tr><tr><td>TOP SOIL</td><td>0</td><td>3</td><td>BLACK</td><td>SOFT</td></tr><tr><td>SAND GRAVEL</td><td>3</td><td>35</td><td>BROWN</td><td>SOFT</td></tr><tr><td>CLAY</td><td>35</td><td>50</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND GRAVEL</td><td>50</td><td>55</td><td>GRAY</td><td>SOFT</td></tr><tr><td>CLAY</td><td>55</td><td>75</td><td>GRAY</td><td>SOFT</td></tr><tr><td>SAND GRAVEL</td><td>75</td><td>100</td><td>GRAY</td><td>SOFT</td></tr></table>						Geological Material	From	To (ft.)	Color	Hardness	TOP SOIL	0	3	BLACK	SOFT	SAND GRAVEL	3	35	BROWN	SOFT	CLAY	35	50	GRAY	SOFT	SAND GRAVEL	50	55	GRAY	SOFT	CLAY	55	75	GRAY	SOFT	SAND GRAVEL	75	100	GRAY	SOFT
Geological Material	From	To (ft.)	Color	Hardness																																				
TOP SOIL	0	3	BLACK	SOFT																																				
SAND GRAVEL	3	35	BROWN	SOFT																																				
CLAY	35	50	GRAY	SOFT																																				
SAND GRAVEL	50	55	GRAY	SOFT																																				
CLAY	55	75	GRAY	SOFT																																				
SAND GRAVEL	75	100	GRAY	SOFT																																				
Well Depth 100 ft.						Depth Completed 100 ft.	Date Well Completed 12/02/2025																																	
Drill Method Non-specified Rotary		Drill Fluid Qwik gel																																						
Use domestic				Status Active																																				
Well Hydrofractured? Yes ☐ No ☒ From To																																								
Casing Type Single casing Joint																																								
Drive Shoe? Yes ☐ No ☒ Above/Below																																								
Casing Diameter 4 in. To 90 ft.		Weight lbs./ft.		Hole Diameter 6.7 in. To 100 ft.																																				
Open Hole From ft. To ft.																																								
Screen? ☒ Type plastic Make BIGFOOT																																								
Diameter 4 in.		Slot/Gauze 15		Length 10 ft.																																				
				Set 90 ft. 100 ft.																																				
Static Water Level 24 ft. land surface Measure 11/20/2025																																								
Pumping Level (below land surface) 90 ft. 1 hrs. Pumping at 100 g.p.m.																																								
Wellhead Completion Pitless adapter manufacturer BAKER Model BULLDOG ☐ Casing Protection ☒ 12 in. above grade ☐ At-grade (Environmental Wells and Borings ONLY)																																								
Grouting Information Well Grouted? ☒ Yes ☐ No ☐ Not Specified																																								
Material bentonite		Amount 6 Sacks		From To ft. 50 ft.																																				
Nearest Known Source of Contamination 50 feet Southwest Direction Septic tank/drain field Type																																								
Well disinfected upon completion? ☒ Yes ☐ No																																								
Pump ☐ Not Installed Date Installed 11/20/2025																																								
Manufacturer's name GRUNDFOS																																								
Model Number GF10SQ07-		HP 0.75		Volt 230																																				
Length of drop pipe 60 ft		Capacity 10 g.p.		Typ Submersible																																				
Abandoned Does property have any not in use and not sealed well(s)? ☐ Yes ☒ No																																								
Variance Was a variance granted from the MDH for this well? ☐ Yes ☒ No																																								
Miscellaneous First Bedrock Aquifer Last Strat Depth to Bedrock ft Located by Locate Method System UTM - NAD83, Zone 15, Meters X Y Unique Number Verification Input Date																																								
Angled Drill Hole																																								
Well Contractor Geo Tech of Minnesota, Inc. 1733 MUNSON, A Licensee Business Lic. or Reg. No. Name of Driller																																								